Ultra-Quiet Air Compressors with Storage Tank

No more noisy compressors

- Ultra-quiet operation as low as 30 dB(A)!
- Get clean, dry air
- Instant high-pressure, pulse-free air
- Resist corrosion
- Pressure switch for operation between 90 and 120 psi

What's included: 0.01-µm filter/regulator (adjustable from 0 to 115 psi), safety valve, tank pressure gauge, tank drain, pressure switch, and auto shut-off mechanism. Models 07067-50, -55, -60, and -65 also include an air dryer.

Specifications

Wetted parts: 314 and 316 stainless steel, aluminum
Maximum temperature: 150°F (66°C)
Duty cycle: continuous (oilless models only)

ISO 9001:2008 CERTIFIED SUPPLIER

DRY

Tank size		Max flow		Max pressure		Port size NPT(F)	hp	Power			Noise level	Dimensions (L x W x H)		Shpg wt lb (kg)	Catalog number	Price
gallons	liters	cfm	L/min	psi	bar			VAC	Hz	Amps		in.	cm			
Oil-lubricated compressors																
0.93	3.5	0.7	20	120	8	¼"	0.18	115	50/60	1.9	30	11 x 11 x 11¾	27.9 x 27.9 x 29.8	38 (17.3)	GH-07067-10	
								220		1.05					GH-07067-11	
6.3	24	2.1	60	120	8	¼"	0.5	115	50/60	4.8	40	16 x 16 x 17	40.6 x 40.6 x 43.2	66 (30)	GH-07067-20	
								220		2.4					GH-07067-21	
6.3	24	4.2	120	120	8	¼"	1	115	50/60	9.6	42	27 x 13 x 26	68.5 x 33.0 x 66.0	100 (45.4)	GH-07067-23	
								220		4.8					GH-07067-24	
Oilless compressors																
0.93	3.5	2.5	67	100	7	¼"	0.6	115	50/60	4.9	62	10½ x 13¾ x 13⅜	26.7 x 34.9 x 34.0	46.3 (21)	GH-07067-38	
								220		2.5					GH-07067-39	
0.93	3.5	2.5	67	100	7	¼"	0.6	115	50/60	4.9	56	17½ x 9 x 15½	44.5 x 22.9 x 39.4	28 (17.2)	GH-07067-41	
								220		2.5					GH-07067-42	
6	24		67				0.6	115		4.9	62	16 x 16 x 27	40.6 x 40.6 x 68.5	58 (26.3)	GH-07067-43	
								220		2.5					GH-07067-44	
1.57	6	4.4	110	100	7	¼"	0.8	115	50/60	7.8	57	24 x 13⅜ x 22⅜	61.0 x 34.0 x 56.8	70 (31.8)	GH-07067-40	
								220		4.8					GH-07067-45	

†Features a built-in desiccant dryer providing clean, dry, and particle-free air at –40°F (–40°C) dew point

Oilless Air Compressors

Virtually maintenance-free

A. Diaphragm Air Compressors offer oil-free, cool air, even at maximum duty—air entering the pump does not go near the motor to pick up heat. Ideal for light-duty applications.

What's included: power cord (except model 07054-00); 115 VAC models include plug.

B. Piston Air Compressors provide higher flow rates—up to 11 cfm. Designed to maintain performance, even after extended use. Order optional tank assemblies for these compressors separately online.

What's included: safety valve, filter/silencer, and terminal box (for hard-wiring; no power cord included).

Specifications

Wetted parts: PTFE, stainless steel, and aluminum
Duty cycle: continuous
Maximum temperature: 104°F (40°C)

A
07054-10

B
07054-36

DRY

Max flow		Max pressure		Port size NPT(F)	hp	Power			Noise level	Dimensions (L x W x H)		Shpg wt lb (kg)	Catalog number	Price
cfm	L/min	psi	bar			VAC	Hz	Amps		in.	cm			
A. Diaphragm compressor pumps														
0.52	14.7	2.5	0.2	¼"	1/16	115	60	0.4	62 to 74 dB(A)	7 x 4¼ x 4¾	17.8 x 10.8 x 12.1	6 (2.8)	GH-07054-00	
		50	3.4			220/230	50/60	0.2				8 (3.7)	GH-07054-05	
1.1	31.1	50	3.4	¼"	⅛	115	60	0.8		7⅝ x 5⅛ x 7⅝	19.4 x 13.0 x 19.4	16 (7.3)	GH-07054-10	
		60	4.1			220/240	50	0.4				18 (8.2)	GH-07054-15	
1.9	53.8	60	4.1	¼"	⅓	110/115	50/60	2.2		7⅝ x 6⅝ x 7⅝	19.4 x 16.8 x 19.4	17 (7.8)	GH-07054-18	
						220/240	50	1.1				16 (7.3)	GH-07054-23	
B. Piston compressor pumps														
1.3	36.8	100	6.9	¼"	⅛	115	60	3.9	62 to 74 dB(A)	11⅝ x 5⅝ x 8½	29.5 x 14.2 x 21.6	24 (10.9)	GH-07054-26	
						220	50	1.9				25 (11.4)	GH-07054-27	
3.5	99.1	100	6.9	¼"	½	115/230	60	12/6		14⅛ x 12 x 8⅞	35.8 x 30.5 x 22.5	33 (15.0)	GH-07054-28	
						220/240	50	12/6.6				52 (23.6)	GH-07054-29	
9.1	257.7	100	6.9	⅜"	1½	115/230	60	21.6/10.8	78 to 80 dB(A)	21½ x 12 x 8¾	54.6 x 30.5 x 22.2	75 (34.1)	GH-07054-36	
						220/380	50	6.6/3.3				77 (35.0)	GH-07054-37	