

Cole-Parmer® Hose Barb Fittings Elbow

Cole-Parmer®



Easily change the flow direction with 90° elbow fittings, optimizing layouts in compact systems and preventing kinks. A single barb on each end of the fitting creates a tight seal to keep the tubing in place.

Fittings are available in standard or cleanroom packed options. Cleanroom packed fittings are manufactured, double bagged, and sealed in an ISO Class 7 cleanroom to ensure that the integrity is not compromised. An ISO Class 7 cleanroom utilizes HEPA filtration systems to maintain air cleanliness levels of less than 10,000 particles of 0.5 µm or larger per cubic foot.



CERTIFICATION

Cole-Parmer will provide a certificate of compliance FREE at your request where applicable.

APPLICATIONS

- Bioprocessing fluid transfer, peristaltic pump systems, and general lab applications
- General-purpose, laboratory, and single-use applications

FEATURES/BENEFITS

- Single barb design tightly “grips” the tubing
- Quick and easy assembly without tools
- Easily change the flow direction with 90° elbows

WARNING: This product is not approved or intended for, and should not be used for, medical, clinical, surgical, or other patient-oriented applications.

USA	+1.800.323.4340 +1.847.549.7600
Canada	+1.800.363.5900
China	86.21.5109.9909
India	+1.800.266.1244

UK	+44 (0) 1480.272279 +33 (0) 1.87170142*
Italy	+49 (0) 937.792030*
All others	+39.02.84349215 +1.847.549.7600

Cole-Parmer®
coleparmer.com

*Inquiries from Germany and France are now handled in our St. Neots office by native-speaking experts.

Materials

PVDF (Kynar®)

- Excellent chemical resistance
- Temperature range: -35 to 135 °C (-31 to 275 °F)
- Sterilize by ethylene oxide (EtO) or autoclave

Its trade name, Kynar, often refers to PVDF (polyvinylidene fluoride). PVDF is a high-purity engineering thermoplastic with excellent chemical resistance, abrasion resistance, flame resistance, and UV stability. PVDF is widely used for chemical tank liners and semiconductor equipment components.

Polypropylene (PP)

- Very good chemical resistance
- Temperature range: -23 to 66 °C (-9 to 150 °F)
- Sterilize by ethylene oxide (EtO) or gamma irradiation

Polypropylene is resistant to weak inorganic acids, organic acids, alcohols, ammonia, and oxidizing salts and has limited resistance to aliphatic hydrocarbons, esters, ketones, and ethers. Polypropylene is generally not recommended for aromatic and halogenated hydrocarbons.

Nylon

- Good chemical resistance
- Temperature range: -46 to 121 °C (-50 to 250 °F)
- Sterilize by ethylene oxide (EtO)

Nylon is resistant to various chemicals, especially aliphatic and aromatic hydrocarbons, alkalis, greases, fuels, lubricants, and ketones. These nylon fittings are made from the same resin as natural nylon, but with FDA-compliant white coloring. They offer good tensile strength, stiffness, and impact resistance.


Polycarbonate (PC)

- Very good chemical resistance
- Sterilize by ethylene oxide (EtO) or gamma irradiation

Polycarbonate offers very good chemical resistance to many aqueous solutions, diluted acids, alcohols, and non-aromatic hydrocarbons while maintaining excellent clarity and impact strength. Polycarbonate is well suited for applications requiring durability, dimensional stability, and visual inspection of flow paths.

Fittings

For additional options and complete offering, visit coleparmer.com.



Elbow Fitting

Specification and Ordering Table

Fitting Type	Tubing ID (A)	Tubing ID (B)	Cleanroom Packed	Material	Color	Item Number	Pack Size
Elbow	1/16"	1/16"	N	Polycarbonate	Natural	50139-81	10
	3/32"	3/32"	N	Polycarbonate	Natural	50139-82	10
	1/8"	1/8"	N	Polycarbonate	Natural	50139-83	10
	5/32"	5/32"	N	Polycarbonate	Natural	50139-84	10
	3/16"	3/16"	N	Polycarbonate	Natural	50139-85	10
	1/4"	1/4"	N	Polycarbonate	Natural	50139-86	10
Reducing Elbow	3/32"	1/16"	Y	Polypropylene	Translucent	50117-33	10
	1/8"	1/16"	Y	Polypropylene	Translucent	50117-36	10
	1/8"	3/32"	Y	Nylon	White	50117-45	10
	1/8"	3/32"	Y	Polypropylene	Translucent	50117-35	10
	3/16"	1/8"	Y	Polypropylene	Translucent	50117-37	10
	1/4"	1/8"	Y	Nylon	White	50117-46	10
	3/8"	1/4"	Y	PVDF	Natural	50117-42	10
	3/8"	1/4"	Y	Polypropylene	Translucent	50117-38	10
	1/2"	1/4"	Y	PVDF	Natural	50117-43	10
	1/2"	1/4"	Y	Polypropylene	Translucent	50117-39	10
	1/2"	3/8"	Y	PVDF	Natural	50117-44	10
	1/2"	3/8"	Y	Polypropylene	Translucent	50117-40	10
	1"	3/4"	Y	PVDF	Natural	50117-41	10
	1"	3/4"	Y	Polypropylene	Translucent	50117-34	10