

# Material Safety Data Sheet

## [Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

ACC# 08704

### Section 1 - Chemical Product and Company Identification

**MSDS Name:** [Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

**Catalog Numbers:** AC368960000, AC368960050, AC368960250

**Synonyms:** Deoxo-Fluor (TM).

#### Company Identification:

Acros Organics N.V.  
One Reagent Lane  
Fair Lawn, NJ 07410

**For information in North America, call:** 800-ACROS-01

**For emergencies in the US, call CHEMTREC:** 800-424-9300

### Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ELINCS
108-88-3	Toluene	50	203-625-9
202289-38-1	[Bis(2-methoxyethyl)amino]sulfur trifluoride	50	unlisted

### Section 3 - Hazards Identification

#### EMERGENCY OVERVIEW

Not available.

**Target Organs:** Respiratory system, eyes, skin.

#### Potential Health Effects

**Eye:** Causes eye burns.

**Skin:** Causes skin burns.

**Ingestion:** Causes gastrointestinal tract burns.

**Inhalation:** Harmful if inhaled. Causes chemical burns to the respiratory tract.

**Chronic:** Not available.

### Section 4 - First Aid Measures

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

**Skin:** Get medical aid immediately. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

**Ingestion:** Do not induce vomiting. Get medical aid immediately.

**Inhalation:** Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

**Notes to Physician:** Treat symptomatically and supportively.

### Section 5 - Fire Fighting Measures

**General Information:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Water reactive. Material will react with water and may release a flammable and/or toxic gas. Flammable liquid and vapor.

**Extinguishing Media:** Do NOT use water directly on fire. Use foam, dry chemical, or carbon dioxide.

**Flash Point:** 4 deg C ( 39.20 deg F)

**Autoignition Temperature:** Not available.

**Explosion Limits, Lower:** Not available.

**Upper:** Not available.

**NFPA Rating:** 2 - health, 3 - flammability, 0 - instability

### Section 6 - Accidental Release Measures

**General Information:** Use proper personal protective equipment as indicated in Section 8.

**Spills/Leaks:** Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container.

### Section 7 - Handling and Storage

**Handling:** Do not breathe dust, vapor, mist, or gas. Do not get in eyes, on skin, or on clothing. Use only in a chemical fume hood.  
**Storage:** Store in a cool, dry place. Store in a tightly closed container. Water free area. Store under an inert atmosphere.

## Section 8 - Exposure Controls, Personal Protection

**Engineering Controls:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low.

### Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Toluene	50 ppm TWA; Skin - potential significant contribution to overall exposure by the cutaneous route	100 ppm TWA; 375 mg/m <sup>3</sup> TWA 500 ppm IDLH	200 ppm TWA; 300 ppm Ceiling
[Bis(2-methoxyethyl)amino]sulfur trifluoride	none listed	none listed	none listed

**OSHA Vacated PELs:** Toluene: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA [Bis(2-methoxyethyl)amino]sulfur trifluoride: No OSHA Vacated PELs are listed for this chemical.

### Personal Protective Equipment

**Eyes:** Not available.

**Skin:** Wear appropriate protective gloves to prevent skin exposure.

**Clothing:** Wear appropriate protective clothing to prevent skin exposure.

**Respirators:** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

## Section 9 - Physical and Chemical Properties

**Physical State:** Liquid

**Appearance:** brown

**Odor:** Not available.

**pH:** Not available.

**Vapor Pressure:** Not available.

**Vapor Density:** Not available.

**Evaporation Rate:** Not available.

**Viscosity:** Not available.

**Boiling Point:** Not available.

**Freezing/Melting Point:** Not available.

**Decomposition Temperature:** Not available.

**Solubility:** Reacts.

**Specific Gravity/Density:** 1.200

**Molecular Formula:** C<sub>6</sub>H<sub>14</sub>F<sub>3</sub>NO<sub>2</sub>S

**Molecular Weight:** 221.24

## Section 10 - Stability and Reactivity

**Chemical Stability:** Stable under normal temperatures and pressures.

**Conditions to Avoid:** Incompatible materials, temperatures above 100°C, exposure to moist air or water.

**Incompatibilities with Other Materials:** Strong oxidizing agents, strong bases, alcohols.

**Hazardous Decomposition Products:** Nitrogen oxides, carbon monoxide, oxides of sulfur, carbon dioxide, hydrogen fluoride gas.

**Hazardous Polymerization:** Has not been reported

## Section 11 - Toxicological Information

### RTECS#:

**CAS#** 108-88-3: XS5250000

**CAS#** 202289-38-1 unlisted.

### LD50/LC50:

**CAS#** 108-88-3:

Draize test, rabbit, eye: 870 ug Mild;  
Draize test, rabbit, eye: 2 mg/24H Severe;  
Draize test, rabbit, skin: 435 mg Mild;  
Draize test, rabbit, skin: 500 mg Moderate;  
Draize test, rabbit, skin: 20 mg/24H Moderate;  
Inhalation, mouse: LC50 = 400 ppm/24H;  
Inhalation, mouse: LC50 = 30000 mg/m<sup>3</sup>/2H;  
Inhalation, mouse: LC50 = 19900 mg/m<sup>3</sup>/7H;  
Inhalation, mouse: LC50 = 10000 mg/m<sup>3</sup>;  
Inhalation, rat: LC50 = 49 gm/m<sup>3</sup>/4H;  
Oral, rat: LD50 = 636 mg/kg;  
Skin, rabbit: LD50 = 14100

**CAS#** 202289-38-1:

### Carcinogenicity:

**CAS#** 108-88-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

**CAS#** 202289-38-1: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

**Epidemiology:** No data available.

**Teratogenicity:** In an epidemiologic study of toluene and pregnancy, occupational exposures to toluene were said to be associated with an increased incidence of renal, urinary, gastrointestinal, and cardiac anomalies. Fetotoxicity (reduced fetal weight), behavioural effects (effects on learning and memory) and hearing loss (in males) were observed in the offspring of rats exposed by inhalation to toluene, in the absence of maternal toxicity.

**Reproductive Effects:** Many reports of reproductive effects of toluene abuse or heavy occupational exposure are confounded by mixed solvent exposure or fetal alcohol syndrome. Women exposed to toluene in lab work had a 4.7-fold increased risk of spontaneous abortions.

**Mutagenicity:** No data available.

**Neurotoxicity:** No data available.

**Other Studies:**

## Section 12 - Ecological Information

No information available.

## Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**RCRA P-Series:** None listed.

**RCRA U-Series:**

CAS# 108-88-3: waste number U220.

## Section 14 - Transport Information

	<b>US DOT</b>	<b>Canada TDG</b>
<b>Shipping Name:</b>	DOT regulated - small quantity provisions apply (see 49CFR173.4)	No information available.
<b>Hazard Class:</b>		
<b>UN Number:</b>		
<b>Packing Group:</b>		

## Section 15 - Regulatory Information

### US FEDERAL

#### TSCA

CAS# 108-88-3 is listed on the TSCA inventory.

CAS# 202289-38-1 is listed on the TSCA inventory.

#### Health & Safety Reporting List

CAS# 108-88-3: Effective 10/4/82, Sunset 10/4/92

#### Chemical Test Rules

None of the chemicals in this product are under a Chemical Test Rule.

#### Section 12b

None of the chemicals are listed under TSCA Section 12b.

#### TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

#### CERCLA Hazardous Substances and corresponding RQs

CAS# 108-88-3: 1000 lb final RQ; 454 kg final RQ

#### SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

#### SARA Codes

CAS # 108-88-3: immediate, fire.

#### Section 313

This material contains Toluene (CAS# 108-88-3, 50%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

#### Clean Air Act:

CAS# 108-88-3 is listed as a hazardous air pollutant (HAP).

This material does not contain any Class 1 Ozone depleters.

This material does not contain any Class 2 Ozone depleters.

#### Clean Water Act:

CAS# 108-88-3 is listed as a Hazardous Substance under the CWA. CAS# 108-88-3 is listed as a Priority Pollutant under the Clean Water Act. CAS# 108-88-3 is listed as a Toxic Pollutant under the Clean Water Act.

#### OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

#### STATE

CAS# 108-88-3 can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts.

CAS# 202289-38-1 is not present on state lists from CA, PA, MN, MA, FL, or NJ.

#### California Prop 65

WARNING: This product contains Toluene, a chemical known to the state of California to cause developmental reproductive toxicity. California No Significant Risk Level: None of the chemicals in this product are listed.

**European/International Regulations**  
**European Labeling in Accordance with EC Directives**

**Hazard Symbols:**

F C

**Risk Phrases:**

- R 11 Highly flammable.
- R 14 Reacts violently with water.
- R 34 Causes burns.
- R 20 Harmful by inhalation.
- R 63 Possible risk of harm to the unborn child.
- R 67 Vapours may cause drowsiness and dizziness.

**Safety Phrases:**

- S 16 Keep away from sources of ignition - No smoking.
- S 25 Avoid contact with eyes.
- S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S 8 Keep container dry.

**WGK (Water Danger/Protection)**

- CAS# 108-88-3: 2
- CAS# 202289-38-1: No information available.

**Canada - DSL/NDSL**

- CAS# 108-88-3 is listed on Canada's DSL List.

**Canada - WHMIS**

- WHMIS: Not available.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

**Canadian Ingredient Disclosure List**

- CAS# 108-88-3 is listed on the Canadian Ingredient Disclosure List.

## Section 16 - Additional Information

**MSDS Creation Date:** 6/10/2003

**Revision #1 Date:** 3/22/2006

*The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of such damages.*