

## Safety Data Sheet

acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

### 1 Identification

- **Product identifier**
- **Trade name:** Double Bubble Urethane High Peel Strength D50 Part A (04022)
- **Relevant identified uses of the substance or mixture.** Adhesive
- **Application of the substance / the mixture** Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Royal Adhesives & Sealants  
800 E. Anaheim Street  
Wilmington, CA 90744  
(310) 830-9904
- **Information department:** Environment protection department.
- **Emergency telephone number:**  
ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.  
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

Repr. 1 H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger

- **Hazard statements**

Causes skin irritation.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 1)

*Causes serious eye irritation.*

*May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

*May cause an allergic skin reaction.*

*Suspected of causing cancer.*

*May damage fertility or the unborn child.*

*May cause respiratory irritation.*

*May cause damage to organs through prolonged or repeated exposure.*

**Precautionary statements**

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*[In case of inadequate ventilation] wear respiratory protection.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Contaminated work clothing must not be allowed out of the workplace.*

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Specific treatment (see on this label).*

*If experiencing respiratory symptoms: Call a POISON CENTER/doctor.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*Call a POISON CENTER/doctor if you feel unwell.*

*Wash contaminated clothing before reuse.*

*IF exposed or concerned: Get medical advice/attention.*

*If skin irritation or rash occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

*Get medical advice/attention if you feel unwell.*

*IF ON SKIN: Wash with plenty of water.*

*Take off contaminated clothing and wash it before reuse.*

*Store locked up.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**Classification system:**

**NFPA ratings (scale 0 - 4)**



**HMIS-ratings (scale 0 - 4)**



**Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Description:** Mixture

(Contd. on page 3)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 2)

**Hazardous components:**

101-68-8	4,4'-methylenediphenyl diisocyanate	5-20%
85-68-7	Butyl Benzyl Phthalate	5-20%

## 4 First-aid measures

**Description of first aid measures**

**After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:**

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

**After swallowing:** Seek medical treatment.

**Information for doctor:**

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing media**

**Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

**Advice for firefighters**

**Protective equipment:** Protective clothing and respiratory protective device.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**Protective Action Criteria for Chemicals**

**PAC-1:**

101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m <sup>3</sup>
85-68-7	Butyl Benzyl Phthalate	15 mg/m <sup>3</sup>

**PAC-2:**

101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m <sup>3</sup>
85-68-7	Butyl Benzyl Phthalate	77 mg/m <sup>3</sup>

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 3)

**PAC-3:**

101-68-8 4,4'-methylenediphenyl diisocyanate

55 mg/m<sup>3</sup>

85-68-7 Butyl Benzyl Phthalate

460 mg/m<sup>3</sup>

## 7 Handling and storage

**Handling:**

**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

**Information about protection against explosions and fires:**

Product reacts with water. Reaction may produce heat and/or gases.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location away from direct heat.

Protect from moisture. Keep packages dry.

**Information about storage in one common storage facility:**

Store away from oxidizing agents.

Keep away from open flames and high temperatures.

**Further information about storage conditions:**

Keep receptacle tightly sealed.

Protect from humidity and water.

Store in dry conditions.

**Specific end use(s) No further relevant information available.**

## 8 Exposure controls/personal protection

**Additional information about design of technical systems: No further data.**

**Control parameters**

**Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

**101-68-8 4,4'-methylenediphenyl diisocyanate**

PEL Ceiling limit value: 0.2 mg/m<sup>3</sup>, 0.02 ppm

REL Long-term value: 0.05 mg/m<sup>3</sup>, 0.005 ppm

Ceiling limit value: 0.2\* mg/m<sup>3</sup>, 0.02\* ppm  
\*10-min

TLV Long-term value: 0.051 mg/m<sup>3</sup>, 0.005 ppm

**Additional information: The lists that were valid during the creation were used as basis.**

**Exposure controls**

**Personal protective equipment (see listings below)**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 4)

• **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• **Material of gloves**

Chloroprene rubber, CR

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Safety glasses with side shields.

• **Body protection:** Protective work clothing

## 9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:

Liquid

Color:

Amber

• **Odor:**

Characteristic

• **Odor threshold:**

Not determined.

• **pH-value:**

Not determined.

• **Change in condition**

Melting point:

Undetermined.

Boiling point:

Undetermined

• **Flash point:**

> 204 °C (> 399 °F)

• **Flammability (solid, gaseous):**

Not applicable.

• **Ignition temperature:**

435 °C (815 °F)

• **Decomposition temperature:**

Not determined.

• **Auto igniting:**

Product is not selfigniting.

• **Danger of explosion:**

Product does not present an explosion hazard.

• **Flammable limits:**

Lower:

0.4 Vol %

Upper:

3.2 Vol %

• **Vapor pressure at 20 °C (68 °F):**

1 hPa (1 mm Hg)

• **Specific gravity at 20 °C (68 °F):**

1.11 g/cm<sup>3</sup> (9.263 lbs/gal)

(Contd. on page 6)

USA



# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 5)

· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC (Per EPA 24)</b>	1.665 GMS/L
· <b>Solids content:</b>	Not available.
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Moisture
- **Possibility of hazardous reactions**  
Contact with moisture, other materials that react with isocyanates, or temperatures above 350F, may cause polymerization.
- **Conditions to avoid** Avoid high temperatures. Avoid freezing.
- **Incompatible materials:**  
Reacts with amines.  
Reacts with alcohols.  
Reacts with alkali (lyes).  
Reacts with water.  
Copper and copper alloys.  
May produce violent reactions with bases and numerous organic substances including alcohols and amines.
- **Hazardous decomposition products:**  
Carbon monoxide  
Carbon dioxide  
Isocyanate  
Isocyanic acid

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**  
**101-68-8 4,4'-methylenediphenyl diisocyanate**
- Oral LD50 2200 mg/kg (mouse)
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**  
Inhalation - Sensitization possible through inhalation.

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 6)

*Skin Contact - Sensitization possible through skin contact.*

· **Additional toxicological information:**

*The product shows the following dangers according to internally approved calculation methods for preparations:*

*Harmful*

*Irritant*

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

101-68-8 4,4'-methylenediphenyl diisocyanate

3

85-68-7 Butyl Benzyl Phthalate

3

· **NTP (National Toxicology Program)**

*None of the ingredients is listed.*

· **OSHA-Ca (Occupational Safety & Health Administration)**

*None of the ingredients is listed.*

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** *No further relevant information available.*

· **Persistence and degradability** *No further relevant information available.*

· **Behavior in environmental systems:**

· **Bioaccumulative potential** *No further relevant information available.*

· **Mobility in soil** *No further relevant information available.*

· **Additional ecological information:**

· **General notes:** *At present there are no ecotoxicological assessments.*

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

· **Other adverse effects** *No further relevant information available.*

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:** *Must be specially treated adhering to official regulations.*

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

## 14 Transport information

· **UN-Number**

· **DOT, ADN, IMDG, IATA**

*not regulated*

· **UN proper shipping name**

· **DOT, ADN, IMDG, IATA**

*not regulated*

· **Transport hazard class(es)**

· **DOT, ADN, IMDG, IATA**

· **Class**

*not regulated*

(Contd. on page 8)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 7)

- |   |                 |
|---|-----------------|
| <b>· Packing group</b>  |                 |
| <b>· DOT, IMDG, IATA</b>  | not regulated   |
| <b>· Environmental hazards:</b>   | Not applicable. |
| <b>· Special precautions for user</b>   | Not applicable. |
| <b>· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | Not applicable. |
| <b>· UN "Model Regulation":</b>   | not regulated   |

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

**· Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**· Section 313 (Specific toxic chemical listings):**

101-68-8 4,4'-methylenediphenyl diisocyanate

**· TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

**· Proposition 65**

**· Chemicals known to cause cancer:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

85-68-7 Butyl Benzyl Phthalate

**· (DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

**· New Jersey Right-to-Know List:**

All ingredients are listed.

**· New Jersey Special Hazardous Substance List:**

85-68-7 Butyl Benzyl Phthalate

CA

**· Pennsylvania Right-to-Know List:**

All ingredients are listed.

**· Pennsylvania Special Hazardous Substance List:**

101-68-8 4,4'-methylenediphenyl diisocyanate

E

85-68-7 Butyl Benzyl Phthalate

E

**· Cancerogenity categories**

**· EPA (Environmental Protection Agency)**

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

(Contd. on page 9)

USA



# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 10/20/2017

Revision Number 2

Revision Date 10/20/2017

**Trade name: Double Bubble Urethane High Peel Strength D50 Part A (04022)**

(Contd. of page 8)

85-68-7	Butyl Benzyl Phthalate	C
<b>TLV (Threshold Limit Value established by ACGIH)</b>		
None of the ingredients listed.		
<b>MAK (German Maximum Workplace Concentration)</b>		
101-68-8	4,4'-methylenediphenyl diisocyanate	4
<b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
None of the ingredients is listed.		

**National regulations:**

- Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

**Department issuing SDS:** Environment protection department.

**Creation Date:** 10/20/2017

**Date of preparation / last revision** 10/20/2017 / 1

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Repr. 1: Reproductive toxicity – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

## Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

### 1 Identification

- **Product identifier**
- **Trade name:** *Double Bubble Urethane High Peel Strength D50 Part B (04022)*
- **Relevant identified uses of the substance or mixture.** *Curing Agent*
- **Application of the substance / the mixture** *Activator*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*Royal Adhesives & Sealants*  
*800 E. Anaheim Street*  
*Wilmington, CA 90744*  
*(310) 830-9904*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:**  
*ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.*  
*Outside USA and Canada: +1 703-527-3887 (collect calls accepted)*

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

*Acute Tox. 4 H302 Harmful if swallowed.*

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS07

- **Signal word** *Warning*
- **Hazard statements**  
*Harmful if swallowed.*
- **Precautionary statements**  
*Wash thoroughly after handling.*  
*Do not eat, drink or smoke when using this product.*  
*If swallowed: Call a poison center/doctor if you feel unwell.*  
*Rinse mouth.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 1

Reactivity = 0

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)

(Contd. of page 1)

## · HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Physical Hazard = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

## 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture

### · Hazardous components:

	polyether polyol	25-50%
1332-58-7	Kaolin	10-25%
13463-67-7	titanium dioxide	≤2.5%

## 4 First-aid measures

- Description of first aid measures
- After inhalation:  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.
- After swallowing: Seek medical treatment.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

## 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:  
Use water fog, dry chemical, foam, Carbon Dioxide.  
Use fire fighting measures that suit the environment.
- Advice for firefighters
- Protective equipment: Protective clothing and respiratory protective device.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures  
Ensure adequate ventilation  
Wear protective clothing.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

**Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)**

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**  
None of the ingredients is listed.

· **PAC-2:**  
None of the ingredients is listed.

· **PAC-3:**  
None of the ingredients is listed.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Use only in well ventilated areas.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location away from direct heat.  
Protect from moisture. Keep packages dry.
- **Information about storage in one common storage facility:**  
Keep away from open flames and high temperatures.  
Store away from oxidizing agents.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Protect from humidity and water.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 1332-58-7 Kaolin

PEL	Long-term value: 15 * 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10 * 5** mg/m <sup>3</sup> *total dust **respirable fraction

(Contd. on page 4)

USA



# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

**Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)**

(Contd. of page 3)

**TLV** Long-term value: 2\* mg/m<sup>3</sup>  
E; as respirable fraction

**13463-67-7 titanium dioxide**

**PEL** Long-term value: 15\* mg/m<sup>3</sup>  
\*total dust

**REL** See Pocket Guide App. A

**TLV** Long-term value: 10 mg/m<sup>3</sup>  
withdrawn from NIC

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment** (see listings below)

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

· **Breathing equipment:** Not necessary if room is well-ventilated.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses with side shields.

· **Body protection:** Protective work clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Color:** Off White

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point:** Undetermined.

**Boiling point:** Undetermined

· **Flash point:** > 96 °C (> 204.8 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 5)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

**Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)**

(Contd. of page 4)

· <b>Ignition temperature:</b>	
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Flammable limits:</b>	
Lower:	Not determined
Upper:	Not determined
· <b>Vapor pressure:</b>	Not determined.
· <b>Specific gravity at 20 °C (68 °F):</b>	1.48 g/cm <sup>3</sup> (12.3506 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	0%
VOC (Per EPA 24)	5.184 GMS/L
· <b>Solids content:</b>	Not available.
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No further information is available.
- **Conditions to avoid** Avoid high temperatures. Avoid freezing.
- **Incompatible materials:** Reacts with oxidizing agents.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** May irritate the skin.
- **on the eye:** May irritate the eye.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- The product is not subject to classification according to internally approved calculation methods for preparations:

(Contd. on page 6)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

**Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)**

(Contd. of page 5)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7 titanium dioxide

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** At present there are no ecotoxicological assessments.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:** Must be specially treated adhering to official regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· **DOT, ADN, IMDG, IATA** not regulated

· **UN proper shipping name**

· **DOT, ADN, IMDG, IATA** not regulated

· **Transport hazard class(es)**

· **DOT, ADN, IMDG, IATA**

· **Class** not regulated

· **Packing group**

· **DOT, IMDG, IATA** not regulated

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Not applicable.

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

**Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)**

(Contd. of page 6)

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** not regulated

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- **TSCA new (21st Century Act) (Substances not listed)**

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

- **New Jersey Right-to-Know List:**

1317-65-3 Limestone

1332-58-7 Kaolin

13463-67-7 titanium dioxide

- **New Jersey Special Hazardous Substance List:**

None of the ingredients is listed.

- **Pennsylvania Right-to-Know List:**

1317-65-3 Limestone

1332-58-7 Kaolin

13463-67-7 titanium dioxide

- **Pennsylvania Special Hazardous Substance List:**

None of the ingredients is listed.

- **Carcinogenicity categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

(Contd. on page 8)



# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 02/08/2018

Revision Number 3

Revision Date 02/08/2018

**Trade name: Double Bubble Urethane High Peel Strength D50 Part B (04022)**

(Contd. of page 7)

<b>TLV (Threshold Limit Value established by ACGIH)</b>		
1332-58-7	Kaolin	A4
13463-67-7	titanium dioxide	A4
<b>MAK (German Maximum Workplace Concentration)</b>		
13463-67-7	titanium dioxide	3A
<b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
13463-67-7	titanium dioxide	

**National regulations:**

- Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

**Department issuing SDS:** Environment protection department.

**Creation Date:** 02/08/2017

**Date of preparation / last revision** 02/08/2018 / 2

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

LATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

LATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

USA