Material Safety Data Sheet Kaolin, acid washed powder, USP

ACC# 12325

Section 1 - Chemical Product and Company Identification

MSDS Name: Kaolin, acid washed powder, USP Catalog Numbers: K2-500, K2-500LOT001

Synonyms: Aluminum silicate (hydrated); Bolus Alba; China clay; Porcelain clay; White Bole.

Company Identification:
Fisher Scientific
Reagent Lane
Fair Lawn, NJ 07410
For information, call: 201-796-7100

Emergency Number: 201-796-7100

For CHEMTREC assistance, call: 800-424-9300

For International CHEMTREC assistance, call: 703-527-3887

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ELINCS
1332-58-7	Kaolin	100	unlisted

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Appearance: white to yellow solid.

Caution! May cause eye, skin, and respiratory tract irritation. This is expected to be a low hazard for usual industrial handling.

Target Organs: None.

Potential Health Effects

Eye: Dust may cause mechanical irritation. **Skin:** Dust may cause mechanical irritation.

Ingestion: Ingestion of large amounts may cause gastrointestinal irritation. Low hazard for usual industrial handling.

Inhalation: May cause respiratory tract irritation. Low hazard for usual industrial handling. When inhaled as a dust or fume, may cause

benign pneumoconiosis.

Chronic: Chronic inhalation can cause pneumoconiosis.

Section 4 - First Aid Measures

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation develops, get medi cal aid.

Skin: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before reuse.

Ingestion: Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water. Wash mouth out with water. Get medical aid if irritation or symptoms occur.

Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear.

Notes to Physician: Treat symptomatically and supportively.

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Substance is noncombustible.

Extinguishing Media: Use extinguishing media most appropriate for the surrounding fire.

Flash Point: Not applicable.

Autoignition Temperature: Not applicable. **Explosion Limits, Lower:**Not available.

Upper: Not available.

NFPA Rating: (estimated) Health: 1; Flammability: 0; Instability: 0

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container. Clean up spills immediately, observing precautions in the Protective Equipment section. Avoid generating dusty conditions. Provide ventilation.

Section 7 - Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Use with adequate ventilation. Minimize dust generation and accumulation. Avoid contact with eyes, skin, and clothing. Keep container tightly closed. Avoid breathing dust.

Storage: Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. No special precautions indicated.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Kaolin	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and < 1% crystalline silica)	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)3000 mg/m3 IDLH (listed under Silica, amorphous).	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

OSHA Vacated PELs: Kaolin: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to minimize contact with skin.

Respirators: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Section 9 - Physical and Chemical Properties

Physical State: Solid **Appearance:** white to yellow

Odor: none reported **pH:** Not available.

Vapor Pressure: Negligible.
Vapor Density: Not available.
Evaporation Rate:Not applicable.
Viscosity: Not available.
Boiling Point: Not available.
Freezing/Melting Point:3200 deg F
Decomposition Temperature:Not available.

Solubility: Insoluble in water. **Specific Gravity/Density:**1.8 to 2.6 **Molecular Formula:**H2Al2Si2O8-H2O

Molecular Weight: 258.2

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Dust generation, excess heat.

Incompatibilities with Other Materials: Strong acids, strong bases. **Hazardous Decomposition Products:** Silicon dioxide, aluminum oxide.

Hazardous Polymerization: Has not been reported.

Section 11 - Toxicological Information

RTECS#:

CAS# 1332-58-7: GF1670500

LD50/LC50: Not available.

Carcinogenicity:

CAS# 1332-58-7: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Epidemiology: No information available.
Teratogenicity: No information available.
Reproductive Effects: No information available.
Mutagenicity: No information available.
Neurotoxicity: No information available.

Other Studies:

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed. RCRA U-Series: None listed.

Section 14 - Transport Information

	US DOT	Canada TDG	
Shipping Name:	Not regulated as a hazardous material	No information available.	
Hazard Class:			
UN Number:			
Packing Group:			

Section 15 - Regulatory Information

US FEDERAL

TSCA

CAS# 1332-58-7 is listed on the TSCA inventory.

Health & Safety Reporting List

None of the chemicals are on the Health & Safety Reporting List.

Chemical Test Rules

None of the chemicals in this product are under a Chemical Test Rule.

Section 12b

None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQs

None of the chemicals in this material have an RQ.

SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

Section 313 No chemicals are reportable under Section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

This material does not contain any Class 1 Ozone depletors.

This material does not contain any Class 2 Ozone depletors.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the CWA.

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

STATE

CAS# 1332-58-7 can be found on the following state right to know lists: California, (listed as Silica, amorphous), New Jersey, (listed as Silica, amorphous), Pennsylvania, Minnesota, Massachusetts.

California Prop 65

California No Significant Risk Level: None of the chemicals in this product are listed.

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols:

Not available. **Risk Phrases:**

Safety Phrases: S 24/25 Avoid contact with skin and eyes.

S 37 Wear suitable gloves.

S 45 In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

S 28A After contact with skin, wash immediately with plenty of water

WGK (Water Danger/Protection)

CAS# 1332-58-7: 0

Canada - DSL/NDSL

CAS# 1332-58-7 is listed on Canada's DSL List.

Canada - WHMIS

This product has a WHMIS classification of Not controlled..

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian Ingredient Disclosure List

CAS# 1332-58-7 (listed as Silica, amorphous) is listed on the Canadian Ingredient Disclosure List.

Section 16 - Additional Information

MSDS Creation Date: 2/16/1999 **Revision #4 Date:** 10/03/2005

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of such damages.