Material Safety Data Sheet Tetrahydrofuran (inhibited)

ACC# 23010

Section 1 - Chemical Product and Company Identification

MSDS Name: Tetrahydrofuran (inhibited)

Catalog Numbers: AC164240000, AC164240010, AC164240025, AC164240050, AC164240250, AC176630000, AC176630010, AC176630025, AC176630050, AC176630100, AC176630200, AC176630250, AC176635000, AC181500000, AC181500010, AC181502500, AC326970000, AC326970010, AC326970025, AC326971000, AC326972500, AC348450000, AC348450010, AC348450025, AC348451000, AC610900010, AC610911000, BP2623-100, BP2624100, NC9058860, NC9149961, NC9966538, T397-1, T397-20, T397-4, T397-500, T397200, T397RB19, T397RB200, T397RS200, T397RS50, T397SK-4, T400-20, T400-4, T400-500 Synonyms: Diethylene oxide; 1,4-Epoxybutane; Tetramethylene oxide; THF; Oxacyclopentane. Company Identification: Fisher Scientific 1 Reagent Lane Fair Lawn, NJ 07410 For information, call: 201-796-7100 Emergency Number: 201-796-7100 For CHEMTREC assistance, call: 800-424-9300

For International CHEMTREC assistance, call: 703-527-3887

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ELINCS
109-99-9	Tetrahydrofuran	>99	203-726-8
128-37-0	Butylated hydroxytoluene	0.025	204-881-4

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Appearance: colorless liquid. Flash Point: -14 deg C.

Danger! Extremely flammable liquid and vapor. Vapor may cause flash fire. Causes severe eye irritation and possible eye injury. Uninhibited material, or material from which the inhibitor has been removed or reacted, may form explosive peroxides. Causes skin and respiratory tract irritation. May be absorbed through intact skin. May be harmful if swallowed. May cause central nervous system depression. May cause lung damage. May cause liver and kidney damage. Hygroscopic (absorbs moisture from the air). **Target Organs:** Kidneys, central nervous system, liver, lungs, respiratory system, eyes, skin.

Potential Health Effects

Eye: Contact with eyes may cause severe irritation, and possible eye burns. Vapors may cause eye irritation. Damage may be permanent.

Skin: Causes skin irritation. May be absorbed through the skin. If absorbed, causes symptoms similar to those of inhalation. THF is not a skin sensitizer in animals.

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression. **Inhalation:** Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation. Inhalation may cause coughing, difficulty breathing and loss of consciousness. Causes irritation of the mucous membrane and upper respiratory tract. Inhalation of tetrahydrofuran vapors may cause abnormal liver function as detected by laboratory tests. (Dupont)

Chronic: Prolonged or repeated eye contact may cause conjunctivitis. Prolonged or repeated skin contact may cause defatting and dermatitis. May cause liver and kidney damage. May cause lung damage. Narcotic in high concentrations. Data show carcinogenic activity in the liver and kidneys of laboratory animals. The kidney tumors were by a mechanism that has no relevance in humans.

Section 4 - First Aid Measures

Eyes: In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes. Get medical aid immediately. **Skin:** In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical aid.

Inhalation: İf inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Notes to Physician: Treat symptomatically and supportively. Persons with skin problems or liver, kidney, lung, or blood diseases may be at increased risk from exposure to this substance.

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Use water spray to keep fire-exposed containers cool. Forms peroxides of unknown stability. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and

flash back. Vapors can spread along the ground and collect in low or confined areas. **Extinguishing Media:** Water may be ineffective. In case of fire, use carbon dioxide, dry chemical powder or appropriate foam. **Flash Point:** -14 deg C (6.80 deg F) **Autoignition Temperature:** 321 deg C (609.80 deg F) **Explosion Limits, Lower:**2.0 vol % **Upper:** 11.8 vol % **NFPA Rating:** (estimated) Health: 2; Flammability: 3; Instability: 1

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Use water spray to dilute spill to a non-flammable mixture. Avoid runoff into storm sewers and ditches which lead to waterways. Remove all sources of ignition. Use a spark-proof tool. Isolate area and deny entry. Provide ventilation. A vapor suppressing foam may be used to reduce vapors.

Section 7 - Handling and Storage

Handling: Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Take precautionary measures against static discharges. Keep container tightly closed. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Keep away from heat, sparks and flame. Avoid breathing vapor or mist. Do not get in eyes. Avoid contact with skin and clothing.

Storage: Keep away from heat, sparks, and flame. Store in a cool place in the original container and protect from sunlight. Keep under a nitrogen blanket. Keep from contact with oxidizing materials. Flammables-area. Regularly check inhibitor levels to maintain peroxide levels below 1%. Store protected from moisture. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. All peroxidizable substances should be stored away from heat and light and be protected from ignition sources.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. **Exposure Limits**

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs	
Tetrahydrofuran	50 ppm TWA; 100 ppm STEL; Skin - potential significant contribution to overall exposure by the cutaneous r oute	200 ppm TWA; 590 mg/m3 TWA 2000 ppm IDLH	200 ppm TWA; 590 mg/m3 TWA	
Butylated hydroxytoluene	2 mg/m3 TWA (inhalable fraction and vapor)	10 mg/m3 TWA	none listed	

OSHA Vacated PELs: Tetrahydrofuran: 200 ppm TWA; 590 mg/m3 TWA Butylated hydroxytoluene: 10 mg/m3 TWA **Personal Protective Equipment**

Eyes: Wear chemical splash goggles.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Section 9 - Physical and Chemical Properties

Physical State: liquid Appearance: colorless Odor: ether-like pH: ~7 (in aq soln) Vapor Pressure: 145 mm Hg @ 20 deg C Vapor Density: 2.5 (air = 1) Evaporation Rate:>1 (Butyl Acetate = 1) Viscosity: 0.48 cP @ 20C Boiling Point: 66 deg C Freezing/Melting Point:-108.5 deg C Decomposition Temperature:Not available. Solubility: Soluble. Specific Gravity/Density:0.89 Molecular Formula:C4H80 Molecular Weight:72.10

Section 10 - Stability and Reactivity

Chemical Stability: Under normal storage conditions, peroxidizable compounds can form and accumulate peroxides which may explode

when subjected to heat or shock. This material is most hazardous when peroxide levels are concentrated by distillation or evaporation. THF should never be distilled to dryness. Prolonged exposure to air, even from extended storage time, can deplete BHT inhibitor and rapidly accelerate THF-peroxide formation.

Conditions to Avoid: Light, ignition sources, moisture, excess heat, evaporating to near dryness, confined spaces. **Incompatibilities with Other Materials:** Strong oxidizing agents, strong acids, oxygen, bromine, metal halides, lithium tetrahydroaluminate, borane, sodium aluminum hydride, sodium tetrahydroaluminate, caustic alkalis. **Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide. **Hazardous Polymerization:** May occur.

Section 11 - Toxicological Information

RTECS#: CAS# 109-99-9: LU5950000 CAS# 128-37-0: GO7875000 LD50/LC50: CAS# 109-99-9: Inhalation, rat: LC50 = 21000 ppm/3H; Oral, rat: LD50 = 1650 mg/kg; . CAS# 128-37-0: Draize test, rabbit, eye: 100 mg/24H Moderate; Draize test, rabbit, eye: 100 mg/48H Moderate; Oral, mouse: LD50 = 650 mg/kg; Oral, mouse: LD50 = 1040 mg/kg; Oral, rabbit: LD50 = 2100 mg/kg;

Carcinogenicity: CAS# 109-99-9:

- ACGIH: A3 Confirmed animal carcinogen with unknown relevance to humans
- California: Not listed.

Oral, rat: LD50 = 890 mg/kg;

- NTP: Not listed.
- IARC: Not listed.

CAS# 128-37-0: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Epidemiology: No information found

Teratogenicity: Animal data show developmental effects only at exposure levels producing other toxic effects in the adult animal. **Reproductive Effects:** Animal testing for reproductive effects shows no change in reproductive performance. **Mutagenicity:** THF has not produced genetic damage in mammalian cell cultures or in animals. It has not been tested for its ability to cause permanent genetic damage in reproductive cells of mammals (not tested for heritable genetic damage). **Neurotoxicity:** No information found **Other Studies:**

Section 12 - Ecological Information

Ecotoxicity: Fish: Fathead Minnow: LC50 = 2160 mg/L; 96 Hr; Flow through bioassay (pH 7.5)Water flea Daphnia: EC50 =5930 mg/L; 24 Hr; Tetrahydrofuran is not expected to adsorb to suspended matter in the water based on its measured Koc values. This compound should volatilize from water surfaces. An estimated BCF value of 1 suggests that tetrahydrofuran will not bioconcentrate in aquatic organisms.

Environmental: If released to the atmosphere, tetrahydrofuran will exist solely in the vapor phase and is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals and nitrate radicals with half-lives of about 1 and 3 days, respectively. Measured Koc values of 23 and 18 indicate that tetrahydrofuran will have very high mobility in soil. **Physical:** No information available. **Other:** No information available.

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series:

CAS# 109-99-9: waste number U213 (Ignitable waste).

Section 14 - Transport Information

	US DOT	Canada TDG
Shipping Name:	TETRAHYDROFURAN	TETRAHYDROFURAN
Hazard Class:	3	3
UN Number:	UN2056	UN2056
Packing Group:	II	II
Additional Info:		FLASH POINT -14C

Section 15 - Regulatory Information

US FEDERAL

TSCA

CAS# 109-99-9 is listed on the TSCA inventory. CAS# 128-37-0 is listed on the TSCA inventory. Health & Safety Reporting List None of the chemicals are on the Health & Safety Reporting List. **Chemical Test Rules** CAS# 109-99-9: Testing required by manufacturers, processors; Test for Health Effects Section 12b CAS# 109-99-9: Section 4 **TSCA Significant New Use Rule** None of the chemicals in this material have a SNUR under TSCA. CERCLA Hazardous Substances and corresponding ROs CAS# 109-99-9: 1000 lb final RQ; 454 kg final RQ SARA Section 302 Extremely Hazardous Substances None of the chemicals in this product have a TPQ. SARA Codes CAS # 109-99-9: immediate, fire, reactive. CAS # 128-37-0: immediate. No chemicals are reportable under Section 313. Section 313 **Clean Air Act:** This material does not contain any hazardous air pollutants. This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors. **Clean Water Act:** None of the chemicals in this product are listed as Hazardous Substances under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. OSHA: None of the chemicals in this product are considered highly hazardous by OSHA. STATE CAS# 109-99-9 can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts.

CAS# 128-37-0 can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts.

California Prop 65

California No Significant Risk Level: None of the chemicals in this product are listed.

European/International Regulations European Labeling in Accordance with EC Directives

Hazard Symbols:

XIF

Risk Phrases:

- R 11 Highly flammable.
- R 19 May form explosive peroxides.
- R 36/37 Irritating to eyes and respiratory system.

Safety Phrases:

- S 16 Keep away from sources of ignition No smoking.
- S 29 Do not empty into drains.
- S 33 Take precautionary measures against static discharges.

WGK (Water Danger/Protection)

CAS# 109-99-9: 1

CAS# 128-37-0: 1

Canada - DSL/NDSL

- CAS# 109-99-9 is listed on Canada's DSL List.
- CAS# 128-37-0 is listed on Canada's DSL List.

Canada - WHMIS

This product has a WHMIS classification of B2, D2B.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian Ingredient Disclosure List

CAS# 109-99-9 is listed on the Canadian Ingredient Disclosure List.

CAS# 128-37-0 is listed on the Canadian Ingredient Disclosure List.

Section 16 - Additional Information

MSDS Creation Date: 5/28/1999 Revision #6 Date: 3/22/2006

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of used and used.