

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/30/2013 Revision date: 02/23/2017 Supersedes: 04/30/2013

Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixtures

Product name : Sodium Hydroxide, 5.0N (5.0M)

Product code : LC24450

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.

Recommended use : Laboratory chemicals

Restrictions on use : Not for food, drug or household use

1.3. Details of the supplier of the safety data sheet

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation Category 1B H314 Serious eye damage/eye irritation Category 1 H318

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHSU

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P260 - Do not breathe mist, spray, vapors

P264 - Wash exposed skin thoroughly after handling

P280 - Wear eye protection, face protection, protective clothing, protective gloves P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a poison center or doctor/physician

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container to comply with local, state and federal regulations

If inhaled: Remove person to fresh air and keep comfortable for breathing

2.3. Other hazards

Other hazards not contributing to the

classification

: None.

2.4. Unknown acute toxicity (GHS US)

Not applicable

02/23/2017 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

Substances

Not applicable

3.2. **Mixtures**

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	83	Not classified
Sodium Hydroxide	(CAS No) 1310-73-2	17	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of hazard classes and H-statements: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact Immediately call a poison center or doctor/physician. Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to First-aid measures after eye contact

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Rinse mouth.

Most important symptoms and effects, both acute and delayed

: Causes severe skin burns and eye damage. Symptoms/injuries

Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Symptoms/injuries after inhalation

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin. Symptoms/injuries after eye contact Causes serious eye damage.

Symptoms/injuries after ingestion Abdominal pain. Bleeding of the gastrointestinal tract. Burns to the gastric/intestinal mucosa.

Nausea. Possible esophageal perforation.

Symptoms/injuries upon intravenous

administration

Not available.

: Not available. Chronic symptoms

Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

Extinguishing media 5.1.

Suitable extinguishing media : Carbon dioxide. Dry powder. Water spray. Foam. Sand. Unsuitable extinguishing media : Not available. Do not use a heavy water stream.

Special hazards arising from the substance or mixture 5.2.

Fire hazard : Not flammable. Explosion hazard Not available.

Reactivity : Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen). Thermal

decomposition generates: Corrosive vapors.

Advice for firefighters

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any Firefighting instructions

chemical fire. In case of fire, stop leak if safe to do so. When cooling/extinguishing: no water in

the substance. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Not available.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Eliminate ignition sources. Ensure adequate ventilation. Wear self-contained breathing General measures apparatus when entering area unless atmosphere is proved to be safe.

02/23/2017 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment : Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin

contact.

Emergency procedures : Wash contaminated clothes. Evacuate unnecessary personnel. Keep containers closed.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Take up liquid spill into inert absorbent material.

Methods for cleaning up : Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Wash

clothing and equipment after handling. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Remove contaminated clothing immediately. Use

corrosionproof equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process

area to prevent formation of vapor. Do not breathe mist, spray, vapors.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Store in original container. Keep only in the original

container in a cool, well ventilated place away from : incompatible materials.

Incompatible products : Strong acids. metals.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 5 - 30 °C

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: strong acids. metals. metal powders.

Storage area : Keep locked up. Store in a well-ventilated place. Keep only in the original container.

Special rules on packaging : SPECIAL REQUIREMENTS: corrosion-proof.

Packaging materials : Do not store in corrodable metal.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Water (7732-18-5)		
Not applicable		
Sodium Hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³ (Sodium hydroxide; USA; Momentary value; TLV - Adopted Value)
OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³
IDLH	US IDLH (mg/m³)	10 mg/m ³
NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

02/23/2017 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Gloves. Safety glasses. Protective clothing. Head/neck protection.



Hand protection : Wear chemically resistant protective gloves. Wear protective gloves.

Eye protection : Chemical goggles or face shield.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Wear appropriate mask.

Thermal hazard protection : None necessary.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.
Color : clear Colorless

Odor : odorless

Odor threshold : No data available

pH : ≥ 14

Melting point No data available Freezing point No data available Boiling point No data available Flash point No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Non flammable. : No data available Vapor pressure Relative vapor density at 20 °C : No data available Relative density : No data available

Specific gravity / density : 1.19 g/ml

Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Viscosity, kinematic : 2.8 cSt

Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available.
Oxidizing properties : No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen). Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with acids.

10.4. Conditions to avoid

Incompatible materials. Direct sunlight. Extremely high or low temperatures.

02/23/2017 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Sodium Hydroxide, 5.0N (5.0M)

metals. Strong acids.

10.6. Hazardous decomposition products

Sodium oxide. Thermal decomposition generates: Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact

Acute toxicity : Not classified

Couldin Hydroxide, 6.614 (6.611)	
LD50 dermal rabbit	7941 mg/kg
ATE US (dermal)	7941.000 mg/kg body weight
Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000.000 mg/kg body weight
Sodium Hydroxide (1310-73-2)	
ATE US (dermal)	1350.000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: ≥ 14

Serious eye damage/irritation : Causes serious eye damage.

pH: ≥ 14

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

Specific target organ toxicity - single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin. Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Abdominal pain. Bleeding of the gastrointestinal tract. Burns to the gastric/intestinal mucosa.

Nausea. Possible esophageal perforation.

Symptoms/injuries upon intravenous

administration

: Not available.

Chronic symptoms : Not available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

Ecology - water : Toxic to aquatic life.

Sodium Hydroxide, 5.0N (5.0M)	
LC50 fish 1	267 mg/l
EC50 Daphnia 1	238 mg/l

02/23/2017 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium Hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (LC50; Other; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

, and the second of the second		
Sodium Hydroxide, 5.0N (5.0M)		
Persistence and degradability	Not established.	
Water (7732-18-5)		
Persistence and degradability	Not established.	
Sodium Hydroxide (1310-73-2)		
Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the substance available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	

12.3. Bioaccumulative potential

Sodium Hydroxide, 5.0N (5.0M)	
Bioaccumulative potential	Not established.
Water (7732-18-5)	
Bioaccumulative potential	Not established.
Sodium Hydroxide (1310-73-2)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to comply with local, state and federal regulations. Dispose in a

safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1824 Sodium hydroxide solution, 8, II

UN-No.(DOT) : UN1824

Proper Shipping Name (DOT) : Sodium hydroxide solution

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

02/23/2017 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N34 - Aluminum construction materials are not authorized for any part of a packaging which is

normally in contact with the hazardous material T7 - 4 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C

(59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids Other information : No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Sodium Hydroxide, 5.0N (5.0M)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Sodium Hydroxide (1310-73-2)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

CANADA		
Sodium Hydroxide, 5.0N (5.0M)		
WHMIS Classification	Class E - Corrosive Material	
Water (7732-18-5)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Sodium Hydroxide (1310-73-2)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class E - Corrosive Material	

EU-Regulations

No additional information available

National regulations

No additional information available

02/23/2017 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SEC.	TION 16: Other information	
Revisi	on date	: 02/23/2017
Other	information	: None.
Full te	xt of H-phrases: see section 16:	
	H312	Harmful in contact with skin
	H314	Causes severe skin burns and eye damage
	H318	Causes serious eye damage
	H402	Harmful to aquatic life
NFPA	health hazard	: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA	fire hazard	: 0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA	reactivity	: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.
HMIS	III Rating	
Health		: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

SDS US LabChem

Personal protection

Flammability

Physical

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

: 0 Minimal Hazard - Materials that will not burn

hazardous polymerization in the absence of inhibitors.

D - Face shield and eye protection, Gloves, Synthetic apron

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

02/23/2017 EN (English US) 8/8