

Material Safety Data Sheet

Hydrochloric Acid Concentrate

ACC# 95181

Section 1 - Chemical Product and Company Identification

MSDS Name: Hydrochloric Acid Concentrate

Catalog Numbers: NC9857200, SA49, XXSA491LI

Synonyms: Muriatic acid; Chlorohydric acid; Hydrogen chloride; Spirits of salt

Company Identification:

Fisher Scientific

1 Reagent Lane

Fair Lawn, NJ 07410

For information, call: 201-796-7100

Emergency Number: 201-796-7100

For CHEMTREC assistance, call: 800-424-9300

For International CHEMTREC assistance, call: 703-527-3887

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ELINCS
7732-18-5	Water	63.5	231-791-2
7647-01-0	Hydrogen chloride	36.5	231-595-7

Hazard Symbols: T C

Risk Phrases: 23 35

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Appearance: colorless to slight yellow clear liquid. **Danger!** Corrosive. Causes eye and skin burns. May cause severe respiratory tract irritation with possible burns. May cause severe digestive tract irritation with possible burns. May cause fetal effects based upon animal studies. Possible sensitizer. May be harmful if swallowed. Hygroscopic.

Target Organs: Respiratory system, teeth, eyes, skin, circulatory system.

Potential Health Effects

Eye: May cause irreversible eye injury. Vapor or mist may cause irritation and severe burns. Contact with liquid is corrosive to the eyes and causes severe burns. May cause painful sensitization to light.

Skin: May be absorbed through the skin in harmful amounts. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Contact with liquid is corrosive and causes severe burns and ulceration.

Ingestion: May cause circulatory system failure. Causes severe digestive tract burns with abdominal pain, vomiting, and possible death. May cause corrosion and permanent tissue destruction of the esophagus and digestive tract. May be harmful if swallowed.

Inhalation: May cause severe irritation of the respiratory tract with sore throat, coughing, shortness of breath and delayed lung edema. Causes chemical burns to the respiratory tract. Exposure to the mist and vapor may erode exposed teeth. Causes corrosive action on the mucous membranes.

Chronic: Prolonged or repeated skin contact may cause dermatitis. Repeated exposure may cause erosion of teeth. May cause fetal effects. Laboratory experiments have resulted in mutagenic effects. Prolonged exposure may cause conjunctivitis, photosensitization, and possible blindness.

Section 4 - First Aid Measures

Eyes: Get medical aid immediately. Do NOT allow victim to rub or keep eyes closed. Extensive irrigation with water is required (at least 30 minutes). SPEEDY ACTION IS CRITICAL!

Skin: Get medical aid immediately. Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Destroy contaminated shoes.

Ingestion: Do NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately. Give milk of magnesia.

Inhalation: Get medical aid immediately. Remove from exposure to fresh air immediately. If breathing is difficult, give oxygen. Do NOT use mouth-to-mouth resuscitation. If breathing has ceased apply artificial respiration using oxygen and a suitable mechanical device such as a bag and a mask.

Notes to Physician: Do NOT use sodium bicarbonate in an attempt to neutralize the acid.

Antidote: Do NOT use oils or ointments in eye.

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Not flammable, but reacts with most metals to form flammable hydrogen gas. Use water spray to keep fire-exposed containers cool. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas. Reaction with water may generate much heat which will increase the

concentration of fumes in the air. Containers may explode when heated.

Extinguishing Media: For large fires, use water spray, fog, or alcohol-resistant foam. Substance is nonflammable; use agent most appropriate to extinguish surrounding fire. Do NOT get water inside containers. Do NOT use straight streams of water. Most foams will react with the material and release corrosive/toxic gases. Cool containers with flooding quantities of water until well after fire is out. For small fires, use carbon dioxide (except for cyanides), dry chemical, dry sand, and alcohol-resistant foam.

Flash Point: Not applicable.

Autoignition Temperature: Not applicable.

Explosion Limits, Lower:Not available.

Upper: Not available.

NFPA Rating: (estimated) Health: 3; Flammability: 0; Instability: 0

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Large spills may be neutralized with dilute alkaline solutions of soda ash (sodium carbonate, Na₂CO₃), or lime (calcium oxide, CaO). Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. Do not get water inside containers. A vapor suppressing foam may be used to reduce vapors. Cover with dry earth, dry sand, or other non-combustible material followed with plastic sheet to minimize spreading and contact with water.

Section 7 - Handling and Storage

Handling: Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use only in a well-ventilated area. Contents may develop pressure upon prolonged storage. Do not breathe dust, vapor, mist, or gas. Do not get in eyes, on skin, or on clothing. Keep container tightly closed. Do not ingest or inhale. Discard contaminated shoes. Use caution when opening. Keep from contact with moist air and steam.

Storage: Do not store in direct sunlight. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Corrosives area. Do not store in metal containers. Store protected from moisture. Do not store near flammable or oxidizing substances (especially nitric acid or chlorates).

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Water	none listed	none listed	none listed
Hydrogen chloride	5 ppm Ceiling	50 ppm IDLH	5 ppm Ceiling; 7 mg/m ³ Ceiling

OSHA Vacated PELs: Water: No OSHA Vacated PELs are listed for this chemical. Hydrogen chloride: No OSHA Vacated PELs are listed for this chemical.

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear neoprene or polyvinyl chloride gloves to prevent exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

Section 9 - Physical and Chemical Properties

Physical State: Clear liquid

Appearance: colorless to slight yellow

Odor: strong, pungent

pH: 0.01

Vapor Pressure: 5.7 mm Hg @ 0 deg C

Vapor Density: 1.26

Evaporation Rate:> 1.00 (N-butyl acetate)

Viscosity: Not available.

Boiling Point: 81.5-110 deg C @ 760 mmHg

Freezing/Melting Point:-74 deg C

Decomposition Temperature:Not available.

Solubility: Miscible.

Specific Gravity/Density:1.0-1.2

Molecular Formula:HCl.H₂O

Molecular Weight:36.46

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Mechanical shock, incompatible materials, metals, excess heat, exposure to moist air or water, bases.

Incompatibilities with Other Materials: Bases, acetic anhydride, alkali metals, aluminum, amines, copper, copper alloys, fluorine, iron,

sodium hydroxide, steel, sulfuric acid, vinyl acetate, zinc, potassium permanganate, cesium acetylene carbide, rubidium acetylene carbide, rubidium carbide, sodium, chlorosulfonic acid, oleum, carbonates, perchloric acid, calcium phosphide, metal oxides, acetates, cesium carbide, beta-propiolactone, ethyleneimine, propylene oxide, lithium silicides, alcohols + hydrogen cyanide, 2-aminoethanol, ammonium hydroxide, calcium carbide, 1,1-difluoroethylene, ethylene diamine, magnesium boride, mercuric sulfate, silver perchlorate + carbon tetrachloride, uranium phosphide.

Hazardous Decomposition Products: Hydrogen chloride, chlorine, carbon monoxide, carbon dioxide, hydrogen gas.

Hazardous Polymerization: Will not occur.

Section 11 - Toxicological Information

RTECS#:

CAS# 7732-18-5: ZC0110000

CAS# 7647-01-0: MW4025000

LD50/LC50:

Not available.

CAS# 7647-01-0:

Inhalation, mouse: LC50 = 1108 ppm/1H;

Inhalation, rat: LC50 = 3124 ppm/1H;

Oral, rabbit: LD50 = 900 mg/kg;

Carcinogenicity:

CAS# 7732-18-5: Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA. CAS# 7647-01-0:

IARC: IARC Group 3 - not classifiable

Epidemiology: Experimental reproductive effects have been reported.

Teratogenicity: Embryo or Fetus: Stunted fetus, Inhalation, rat TCL0=450 mg/m3/1H Specific Developmental Abnormalities: homeostatis, Inhalation, rat TCL0=450 mg/m3/1H (female 1 days pre-mating).

Reproductive Effects: No information available.

Neurotoxicity: No information available.

Mutagenicity: Cytogenetic analysis: Hamster, lung = 30 mmol/L.; Cytogenetic analysis: Hamster, ovary = 8 mmol/L.

Other Studies: No data available.

Section 12 - Ecological Information

Ecotoxicity: Fish: Bluegill/Sunfish: 3.6 mg/L; 48Hr; Lethal (unspecified) Bluegill/Sunfish: LC50; 96 Hr; pH 3.0-3.5 No data available.

Environmental: Rapidly hydrolyzes when exposed to water. Will exhibit extensive evaporation from soil surfaces. Upon transport through the soil, hydrochloric acid will dissolve some of the soil materials (especially those with carbonate bases) and the acid will neutralize to some degree.

Physical: No information available.

Other: No information available.

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series: None listed.

Section 14 - Transport Information

	US DOT	IATA	RID/ADR	IMO	Canada TDG
Shipping Name:	HYDROCHLORIC ACID				HYDROCHLORIC ACID SOLUTION
Hazard Class:	8				8
UN Number:	UN1789				UN1789
Packing Group:	II				II

Section 15 - Regulatory Information

US FEDERAL

TSCA

CAS# 7732-18-5 is listed on the TSCA inventory.

CAS# 7647-01-0 is listed on the TSCA inventory.

Health & Safety Reporting List

None of the chemicals are on the Health & Safety Reporting List.

Chemical Test Rules

None of the chemicals in this product are under a Chemical Test Rule.

Section 12b

None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

SARA

CERCLA Hazardous Substances and corresponding RQs

CAS# 7647-01-0: 5000 lb final RQ; 2270 kg final RQ

SARA Section 302 Extremely Hazardous Substances

CAS# 7647-01-0: 500 lb TPQ; 5000 lb EPCRA RQ

SARA Codes

CAS # 7647-01-0: acute.

Section 313

This material contains Hydrogen chloride (CAS# 7647-01-0, 36 5%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

Clean Air Act:

CAS# 7647-01-0 is listed as a hazardous air pollutant (HAP). This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors.

Clean Water Act:

CAS# 7647-01-0 is listed as a Hazardous Substance under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

STATE

CAS# 7732-18-5 is not present on state lists from CA, PA, MN, MA, FL, or NJ.

CAS# 7647-01-0 can be found on the following state right to know lists: California, New Jersey, Florida, Pennsylvania, Minnesota, Massachusetts.

California No Significant Risk Level: None of the chemicals in this product are listed.

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols:

T C

Risk Phrases:

R 23 Toxic by inhalation.

R 35 Causes severe burns.

Safety Phrases:

S 1/2 Keep locked up and out of reach of children.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S 9 Keep container in a well-ventilated place.

WGK (Water Danger/Protection)

CAS# 7732-18-5: No information available.

CAS# 7647-01-0: 1

Canada - DSL/NDSL

CAS# 7732-18-5 is listed on Canada's DSL List.

CAS# 7647-01-0 is listed on Canada's DSL List.

Canada - WHMIS

This product has a WHMIS classification of E.

Canadian Ingredient Disclosure List

CAS# 7647-01-0 is listed on the Canadian Ingredient Disclosure List.

Exposure Limits

CAS# 7647-01-0: OEL-AUSTRALIA:TWA 5 ppm (7 mg/m³) OEL-AUSTRIA:TWA 5 ppm (7 mg/m³) OEL-BELGIUM:STEL 5 ppm (7.7 mg/m³) OEL-DENMARK:STEL 5 ppm (7 mg/m³) OEL-FINLAND:STEL 5 ppm (7 mg/m³);Skin OEL-FRANCE:STEL 5 ppm (7.5 mg/m³) OEL-GERMANY:TWA 5 ppm (7 mg/m³) OEL-HUNGARY:STEL 5 mg/m³ OEL-JAPAN:STEL 5 ppm (7.5 mg/m³) OEL-THE NETHERLANDS:TWA 5 ppm (7 mg/m³) OEL-THE PHILIPPINES:TWA 5 ppm (7 mg/m³) OEL-POLAND:TWA 5 mg/m³ OEL-RUSSIA:STEL 5 ppm (5 mg/m³) OEL-SWEDEN:STEL 5 ppm (8 mg/m³) OEL-SWITZERLAND:TWA 5 ppm (7.5 mg/m³);STEL 10 ppm (15 mg/m³) OEL-THAILAND:TWA 5 ppm (7 mg/m³) OEL-TURKEY:TWA 5 ppm (7 mg/m³) OEL-UNITED KINGDOM:TWA 5 ppm (7 mg/m³);STEL 5 ppm (7 mg/m³) OEL IN BULGARIA, COLOMBIA, JORDAN, KOREA check ACGIH TLV OEL IN NEW ZEALAND, SINGAPORE, VIETNAM check ACGI TLV

Section 16 - Additional Information

MSDS Creation Date: 7/06/1999

Revision #3 Date: 11/06/2001

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of such damages.