

Material Safety Data Sheet

Petroleum Ether, Boiling Range 40-65 Degree C, C.P.

ACC# 96205

Section 1 - Chemical Product and Company Identification

MSDS Name: Petroleum Ether, Boiling Range 40-65 Degree C, C.P.

Catalog Numbers: AC124860000, AC124860025, AC124860050

Synonyms: Ligrion, Refined Solvent.

Company Identification:

Acros Organics N.V.

One Reagent Lane

Fair Lawn, NJ 07410

For information in North America, call: 800-ACROS-01

For emergencies in the US, call CHEMTREC: 800-424-9300

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ELINCS
8032-32-4	Ligroine	100	232-453-7

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Appearance: clear, colorless liquid. Flash Point: -30 deg C.

Danger! Extremely flammable liquid and vapor. Vapor may cause flash fire. Harmful if swallowed. Causes eye, skin, and respiratory tract irritation. Prolonged or repeated contact causes defatting of the skin with irritation, dryness, and cracking. Aspiration hazard if swallowed. Can enter lungs and cause damage. May cause lung damage. May cause central nervous system depression. This substance has caused adverse reproductive and fetal effects in animals.

Target Organs: Central nervous system, lungs.

Potential Health Effects

Eye: Causes eye irritation.

Skin: Prolonged and/or repeated contact may cause irritation and/or dermatitis. Exposure may cause irritation characterized by redness, dryness, and inflammation.

Ingestion: Harmful if swallowed. Aspiration hazard. Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

Inhalation: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. High vapor concentrations may cause drowsiness. May cause hemorrhage of vital organs and coma.

Chronic: Prolonged or repeated skin contact may cause dermatitis.

Section 4 - First Aid Measures

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

Skin: Get medical aid immediately. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Ingestion: Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately.

Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to Physician: Treat symptomatically and supportively.

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas.

Extinguishing Media: Use foam, dry chemical, or carbon dioxide. Water may be ineffective. This material is lighter than water and insoluble in water. The fire could easily be spread by the use of water in an area where the water cannot be contained.

Flash Point: -30 deg C (-22.00 deg F)

Autoignition Temperature: 250 deg C (482.00 deg F)

Explosion Limits, Lower: .60 vol %

Upper: 8.00 vol %

NFPA Rating: (estimated) Health: 1; Flammability: 3; Instability: 0

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. A vapor suppressing foam may be used to reduce vapors.

Section 7 - Handling and Storage

Handling: Wash thoroughly after handling. Use only in a well-ventilated area. Ground and bond containers when transferring material. Do not get in eyes, on skin, or on clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep away from heat, sparks and flame. Do not ingest or inhale. Prevent build up of vapors to explosive concentration. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

Storage: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local explosion-proof ventilation to keep airborne levels to acceptable levels.

Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Ligroine	300 ppm TWA	350 mg/m ³ TWA	none listed

OSHA Vacated PELs: Ligroine: 300 ppm TWA; 1350 mg/m³ TWA

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance: clear, colorless

Odor: Mild gasoline like odor

pH: Not available.

Vapor Pressure: Not available.

Vapor Density: Not available.

Evaporation Rate:>1

Viscosity: Not available.

Boiling Point: 40.0 - 65.0 deg C @ 760.00mm

Freezing/Melting Point:-40 deg C

Decomposition Temperature:Not available.

Solubility: insoluble

Specific Gravity/Density:.6530g/cm³

Molecular Formula:Not available.

Molecular Weight:Not available.

Section 10 - Stability and Reactivity

Chemical Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Conditions to Avoid: Ignition sources, excess heat.

Incompatibilities with Other Materials: Oxygen and strong oxidizing agents

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.

Hazardous Polymerization: Has not been reported.

Section 11 - Toxicological Information

RTECS#:

CAS# 8032-32-4: OI6180000

LD50/LC50:

CAS# 8032-32-4:

Inhalation, rat: LC50 = 3400 ppm/4H;

Carcinogenicity:

CAS# 8032-32-4:

- **ACGIH:** A3 - Confirmed animal carcinogen with unknown relevance to humans
- **California:** Not listed.
- **NTP:** Not listed.
- **IARC:** Not listed.

Epidemiology: ACGIH has labeled this substance as a confirmed animal carcinogen.
Teratogenicity: Teratogenic effects have occurred in experimental animals.
Reproductive Effects: No information found
Mutagenicity: No information found
Neurotoxicity: No information found
Other Studies:

Section 12 - Ecological Information

Ecotoxicity: No data available. Not available low potential to affect aquatic organisms, secondary waste treatment microorganisms and the germination of some plants. It has a moderate potential to affect the germination and growth of some plants.
Environmental: Terrestrial Fate: Petroleum Ether will have a low to high mobility in soil. Volatilization of petroleum ether is expected as well. Aquatic Fate: Volatilization from water is rapid. Adsorption to sediment will vary. Bioconcentration in aquatic organisms is not expected to be an important fate process because of expected moderate water solubility. Atmospheric Fate: It will exist primarily as vapor phase degrading by photochemically produced hydroxyl radicals, expected half-life is 4-8 days. Removal may also occur via wet deposition.
Physical: No information found.
Other: No information found.

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.
RCRA P-Series: None listed.
RCRA U-Series: None listed.

Section 14 - Transport Information

	US DOT	Canada TDG
Shipping Name:	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES NOS (PETROLEUM ETHER)
Hazard Class:	3	3
UN Number:	UN1268	UN1268
Packing Group:	II	II
Additional Info:		FP -30 C

Section 15 - Regulatory Information

US FEDERAL

TSCA

CAS# 8032-32-4 is listed on the TSCA inventory.

Health & Safety Reporting List

None of the chemicals are on the Health & Safety Reporting List.

Chemical Test Rules

None of the chemicals in this product are under a Chemical Test Rule.

Section 12b

None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQs

None of the chemicals in this material have an RQ.

SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

SARA Codes

CAS # 8032-32-4: immediate, delayed, fire.

Section 313

No chemicals are reportable under Section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

This material does not contain any Class 1 Ozone depletors.

This material does not contain any Class 2 Ozone depletors.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the CWA.

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

STATE

CAS# 8032-32-4 can be found on the following state right to know lists: New Jersey. Pennsylvania. Minnesota.

California Prop 65

California No Significant Risk Level: None of the chemicals in this product are listed.

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols:

F

Risk Phrases:

R 11 Highly flammable.

Safety Phrases:

S 16 Keep away from sources of ignition - No smoking.
S 29 Do not empty into drains.
S 33 Take precautionary measures against static discharges.
S 9 Keep container in a well-ventilated place.

WGK (Water Danger/Protection)

CAS# 8032-32-4: 1

Canada - DSL/NDSL

CAS# 8032-32-4 is listed on Canada's DSL List.

Canada - WHMIS

This product has a WHMIS classification of B2, D2A, D1B.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian Ingredient Disclosure List

CAS# 8032-32-4 is listed on the Canadian Ingredient Disclosure List.

Section 16 - Additional Information

MSDS Creation Date: 11/17/1997

Revision #7 Date: 7/06/2006

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of such damages.