Material Safety Data Sheet Ethoxytrimethylsilane, 98%

ACC# 98919

Section 1 - Chemical Product and Company Identification

MSDS Name: Ethoxytrimethylsilane, 98%

Catalog Numbers: AC313820000, AC313820050, AC313820250

Synonyms: Silane, Trimethylethoxy-.

Company Identification:
Acros Organics N.V.
One Reagent Lane

Fair Lawn, NJ 07410

For information in North America, call: 800-ACROS-01

For emergencies in the US, call CHEMTREC: 800-424-9300

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ELINCS
1825-62-3	Ethoxytrimethylsilane	98%	217-370-6

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Appearance: colorless clear liquid. Flash Point: -18 deg C.

Danger! Highly flammable. Causes respiratory tract irritation. Irritant. Causes eye and skin irritation. May cause digestive tract irritation. May cause central nervous system depression. Moisture sensitive.

Target Organs: Central nervous system.

Potential Health Effects

Eye: Causes eye irritation. May cause chemical conjunctivitis and comeal damage.

Skin: Causes skin irritation. May cause cyanosis of the extremities.

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Ingestion of large amounts may cause CNS depression.

Inhalation: Causes respiratory tract irritation. Aspiration may lead to pulmonary edema. Vapors may cause dizziness or suffocation.

Inhalation at high concentrations may cause CNS depression and asphixiation. May cause burning sensation in the chest.

Chronic: Effects may be delayed.

Section 4 - First Aid Measures

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin: Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse.

Ingestion: Never give anything by mouth to an unconscious person. Get medical aid. Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water.

Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation.

Notes to Physician: Treat symptomatically and supportively.

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Water may be ineffective. Material is lighter than water and a fire may be spread by the use of water. Will be easily ignited by heat, sparks or flame. Containers may explode if exposed to fire.

Extinguishing Media: For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Water may be ineffective. Water may spread fire. If water is the only media available, use in flooding amounts. For large fires, use water spray, fog or alcohol-resistant foam. Do NOT use straight streams of water. Cool containers with flooding quantities of water until well after fire is out.

Flash Point: -18 deg C (-0.40 deg F)

Autoignition Temperature: 280 deg C (536.00 deg F)

Explosion Limits, Lower:1.50%

Upper: 16.50%

NFPA Rating: (estimated) Health: 2; Flammability: 4; Instability: 0

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. Do not get water inside containers. A vapor suppressing foam may be used to reduce vapors.

Section 7 - Handling and Storage

Handling: Use only in a well-ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Avoid ingestion and inhalation. Do not allow contact with water. Wash clothing before reuse. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep from contact with moist air and steam.

Storage: Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. Store protected from moisture.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local explosion-proof ventilation to keep airborne levels to acceptable levels.

Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Ethoxytrimethylsilane	none listed	none listed	none listed

OSHA Vacated PELs: Ethoxytrimethylsilane: No OSHA Vacated PELs are listed for this chemical.

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Section 9 - Physical and Chemical Properties

Physical State: Clear liquid Appearance: colorless Odor: mild odor

Odor: mild odor **pH:** Not available.

Vapor Pressure: 111 mm Hg @ 25 deg C

Vapor Density: 4.07

Evaporation Rate:Not available. **Viscosity:** Not available.

Boiling Point: 75-76 deg C @ 760mmHg **Freezing/Melting Point:**Not available. **Decomposition Temperature:**Not available.

Solubility: Reacts.

Specific Gravity/Density:.7570g/cm3 Molecular Formula:Si(CH3)3OC2H5 Molecular Weight:118.1829

Section 10 - Stability and Reactivity

Chemical Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Conditions to Avoid: Incompatible materials, ignition sources, moisture, excess heat. **Incompatibilities with Other Materials:** Moisture, acids, peroxides, oxidizing agents. **Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, silicon dioxide.

Hazardous Polymerization: Has not been reported

Section 11 - Toxicological Information

RTECS#:

CAS# 1825-62-3: VV4110000

LD50/LC50: CAS# 1825-62-3:

Draize test, rabbit, eye: 79 mg;

Carcinogenicity:

CAS# 1825-62-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Epidemiology: No information found

Teratogenicity: No information found Reproductive Effects: No information found Mutagenicity: No information found Neurotoxicity: No information found

Other Studies:

Section 12 - Ecological Information

No information available

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed. RCRA U-Series: None listed.

Section 14 - Transport Information

	US DOT	Canada TDG	
Shipping Name:	DOT regulated - small quantity provisions apply (see 49CFR173.4)	No information available.	
Hazard Class:			
UN Number:			
Packing Group:			

Section 15 - Regulatory Information

US FEDERAL

TSCA

CAS# 1825-62-3 is listed on the TSCA inventory.

Health & Safety Reporting List

None of the chemicals are on the Health & Safety Reporting List.

Chemical Test Rules

None of the chemicals in this product are under a Chemical Test Rule.

Section 12b

None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQs None of the chemicals in this material have an RQ

SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

Section 313

No chemicals are reportable under Section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

This material does not contain any Class 1 Ozone depletors.

This material does not contain any Class 2 Ozone depletors.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the CWA.

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA. **STATE**

CAS# 1825-62-3 is not present on state lists from CA, PA, MN, MA, FL, or NJ.

California Prop 65

California No Significant Risk Level: None of the chemicals in this product are listed.

European/International Regulations European Labeling in Accordance with EC Directives

Hazard Symbols:

XI F

Risk Phrases:

R 11 Highly flammable.

R 36/37/38 Irritating to eyes, respiratory system and skin.

Safety Phrases:

- S 16 Keep away from sources of ignition No smoking.
- S 26 In case of contact with eyes, rinse immediately with plenty of

water and seek medical advice.

- S 33 Take precautionary measures against static discharges.
- S 37/39 Wear suitable gloves and eye/face protection.

S 9 Keep container in a well-ventilated place.

WGK (Water Danger/Protection)

CAS# 1825-62-3: No information available.

Canada - DSL/NDSL

CAS# 1825-62-3 is listed on Canada's NDSL List.

Canada - WHMIS

This product has a WHMIS classification of D2B, B2.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian Ingredient Disclosure List

Section 16 - Additional Information

MSDS Creation Date: 11/13/1996 **Revision #7 Date:** 3/04/2004

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of such damages.