

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

1 Identification

- **Product identifier**
- **Trade name:** CLP Analyte Standard
- **Article number:** ANALCS
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
High-Purity Standards
7221 Investment Drive, North Charleston, SC 29418 United States
Telephone: +1-843-767-7900
Fax: +1-843-767-7906
highpuritystandards.com
Email: info@highpuritystandards.com
- **Information department:** Product safety department
- **Emergency telephone number:**
INFOTRAC
Emergency telephone numbers 1-800-535-5053
Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

- Met. Corr.1 H290 May be corrosive to metals.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**
nitric acid
- **Hazard statements**
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
Keep only in original container.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 1)

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

7697-37-2	nitric acid	2.0%
-----------	-------------	------

· **Chemical identification of the substance/preparation**

7439-92-1	lead	0.01%
7440-02-0	nickel	0.01%
7440-22-4	silver	0.01%
7440-43-9	cadmium (non-pyrophoric)	0.01%
7440-66-6	zinc	0.01%
7803-55-6	Ammonium Vanadate	0.005%
513-77-9	barium carbonate	0.005%
543-81-7	beryllium acetate	0.005%
6156-78-1	Manganese(II) acetate tetrahydrate	0.005%
7440-47-3	chromium	0.005%
7440-48-4	cobalt	0.005%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 2)

7440-50-8	copper	0.005%
7732-18-5	water, distilled, conductivity or of similar purity	97.915%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

7697-37-2	nitric acid	0.16 ppm
7439-92-1	lead	0.15 mg/m ³
7440-02-0	nickel	4.5 mg/m ³
7440-22-4	silver	0.3 mg/m ³

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 3)

7440-43-9	<i>cadmium (non-pyrophoric)</i>	0.10 mg/m ³
7440-66-6	<i>zinc</i>	6 mg/m ³
7803-55-6	<i>Ammonium Vanadate</i>	0.01 mg/m ³
513-77-9	<i>barium carbonate</i>	2.2 mg/m ³
6156-78-1	<i>Manganese(II) acetate tetrahydrate</i>	13 mg/m ³
7440-47-3	<i>chromium</i>	1.5 mg/m ³
7440-48-4	<i>cobalt</i>	0.18 mg/m ³
7440-50-8	<i>copper</i>	3 mg/m ³

· PAC-2:

7697-37-2	<i>nitric acid</i>	24 ppm
7439-92-1	<i>lead</i>	120 mg/m ³
7440-02-0	<i>nickel</i>	50 mg/m ³
7440-22-4	<i>silver</i>	170 mg/m ³
7440-43-9	<i>cadmium (non-pyrophoric)</i>	0.76 mg/m ³
7440-66-6	<i>zinc</i>	21 mg/m ³
7803-55-6	<i>Ammonium Vanadate</i>	0.11 mg/m ³
513-77-9	<i>barium carbonate</i>	270 mg/m ³
6156-78-1	<i>Manganese(II) acetate tetrahydrate</i>	22 mg/m ³
7440-47-3	<i>chromium</i>	17 mg/m ³
7440-48-4	<i>cobalt</i>	2 mg/m ³
7440-50-8	<i>copper</i>	33 mg/m ³

· PAC-3:

7697-37-2	<i>nitric acid</i>	92 ppm
7439-92-1	<i>lead</i>	700 mg/m ³
7440-02-0	<i>nickel</i>	99 mg/m ³
7440-22-4	<i>silver</i>	990 mg/m ³
7440-43-9	<i>cadmium (non-pyrophoric)</i>	4.7 mg/m ³
7440-66-6	<i>zinc</i>	120 mg/m ³
7803-55-6	<i>Ammonium Vanadate</i>	80 mg/m ³
513-77-9	<i>barium carbonate</i>	1,600 mg/m ³
6156-78-1	<i>Manganese(II) acetate tetrahydrate</i>	740 mg/m ³
7440-47-3	<i>chromium</i>	99 mg/m ³
7440-48-4	<i>cobalt</i>	20 mg/m ³
7440-50-8	<i>copper</i>	200 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 4)

- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: *CLP Analyte Standard*

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties
· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.· **Flammability (solid, gaseous):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)· **Density at 20 °C (68 °F):** 1.01606 g/cm³ (8.47902 lbs/gal)

· Bulk density:	1,014 kg/m ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.

· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

(Contd. on page 7)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 6)

- **Solvent content:**
 - Water:** 97.9 %
 - VOC content:** 0.00 %
0.0 g/l / 0.00 lb/gal
- **Solids content:** 0.1 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** Strong caustic effect on skin and mucous membranes.
 - **on the eye:**
 - Strong caustic effect.
 - Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Corrosive
 - Irritant
 - Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7439-92-1	lead	2B
7440-02-0	nickel	2B
7440-43-9	cadmium (non-pyrophoric)	1
543-81-7	beryllium acetate	1
7440-47-3	chromium	3
7440-48-4	cobalt	2B

· **NTP (National Toxicology Program)**

7439-92-1	lead	R
7440-02-0	nickel	R

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 7)

7440-43-9	cadmium (non-pyrophoric)	K
543-81-7	beryllium acetate	K
7440-48-4	cobalt	R
· OSHA-Ca (Occupational Safety & Health Administration)		
7440-43-9	cadmium (non-pyrophoric)	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN3264
- **UN proper shipping name**
- **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
- **ADR** 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
- **IMDG, IATA** CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 8 Corrosive substances
· **Label** 8

· **ADR, IMDG, IATA**



· **Class** 8 Corrosive substances
· **Label** 8

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Corrosive substances

· **Danger code (Kemler):** 80

· **EMS Number:** F-A,S-B

· **Segregation groups** Acids

· **Stowage Category** A

· **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

US

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

7697-37-2	nitric acid
-----------	-------------

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	nitric acid
7439-92-1	lead
7440-02-0	nickel
7440-22-4	silver
7440-43-9	cadmium (non-pyrophoric)
7440-66-6	zinc
7803-55-6	Ammonium Vanadate
513-77-9	barium carbonate
543-81-7	beryllium acetate
7440-47-3	chromium
7440-48-4	cobalt
7440-50-8	copper

· **TSCA (Toxic Substances Control Act):**

7697-37-2	nitric acid	ACTIVE
7439-92-1	lead	ACTIVE
7440-02-0	nickel	ACTIVE
7440-22-4	silver	ACTIVE
7440-43-9	cadmium (non-pyrophoric)	ACTIVE
7440-66-6	zinc	ACTIVE
7803-55-6	Ammonium Vanadate	ACTIVE
513-77-9	barium carbonate	ACTIVE
7440-47-3	chromium	ACTIVE
7440-48-4	cobalt	ACTIVE
7440-50-8	copper	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE

· **Hazardous Air Pollutants**

7439-92-1	lead
7440-48-4	cobalt

· **Proposition 65**

· **Chemicals known to cause cancer:**

7439-92-1	lead
7440-02-0	nickel
7440-43-9	cadmium (non-pyrophoric)
543-81-7	beryllium acetate

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 10)

7440-48-4	cobalt
-----------	--------

· **Chemicals known to cause reproductive toxicity for females:**

7439-92-1	lead
-----------	------

· **Chemicals known to cause reproductive toxicity for males:**

7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· **Chemicals known to cause developmental toxicity:**

7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7439-92-1	lead	B2
7440-22-4	silver	D
7440-43-9	cadmium (non-pyrophoric)	B1
7440-66-6	zinc	D, I, II
513-77-9	barium carbonate	D, CBD(inh), NL(oral)
7440-47-3	chromium	D
7440-50-8	copper	D

· **TLV (Threshold Limit Value established by ACGIH)**

7439-92-1	lead	A3
7440-02-0	nickel	A5
7440-43-9	cadmium (non-pyrophoric)	A2
513-77-9	barium carbonate	A4
7440-47-3	chromium	A4
7440-48-4	cobalt	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0	nickel
7440-43-9	cadmium (non-pyrophoric)
543-81-7	beryllium acetate

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05

· **Signal word** Danger

· **Hazard-determining components of labeling:**

nitric acid

· **Hazard statements**

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/11/2019

Reviewed on 11/11/2019

Trade name: CLP Analyte Standard

(Contd. of page 11)

· Precautionary statements*Keep only in original container.**Do not breathe dusts or mists.**Wash thoroughly after handling.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Rinse mouth. Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Immediately call a poison center/doctor.**Specific treatment (see on this label).**Wash contaminated clothing before reuse.**Absorb spillage to prevent material damage.**Store locked up.**Store in corrosive resistant container with a resistant inner liner.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.***16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: *Environment protection department.***· Contact:***High-Purity Standards**Tel: 843-767-7900**Fax: 843-767-7906***· Date of preparation / last revision** *11/11/2019 / -***· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Met. Corr. 1: Corrosive to metals – Category 1**Skin Corr. 1A: Skin corrosion/irritation – Category 1A**Eye Dam. 1: Serious eye damage/eye irritation – Category 1*