

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

1 Identification

- **Product identifier**
- **Product Name:** ICP-MS Instrument Calibration Standard 1A
- **Part Name:** CL-CAL-1A
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**
nitric acid
- **Hazard statements**
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

| | |
|------------|---|
| HEALTH | 3 |
| FIRE | 0 |
| REACTIVITY | 0 |

Health = 3
Fire = 0
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

US

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 1)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|-----------|-------------|------|
| 7697-37-2 | nitric acid | 5.0% |
|-----------|-------------|------|

· **Chemical identification of the substance/preparation**

| | | |
|-----------|---|---------|
| 87-69-4 | (+)-tartaric acid | <0.9% |
| 7782-49-2 | selenium | 0.005% |
| 7440-41-7 | Beryllium from Beryllium Acetate | 0.001% |
| 7440-43-9 | cadmium (non-pyrophoric) | 0.001% |
| 7440-48-4 | cobalt | 0.001% |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate | 0.001% |
| 7440-50-8 | copper | 0.001% |
| 7439-96-5 | manganese | 0.001% |
| 7439-98-7 | molybdenum | 0.001% |
| 7440-02-0 | nickel | 0.001% |
| 7439-92-1 | Lead from Lead Oxide | 0.001% |
| 7440-36-0 | antimony | 0.001% |
| 7440-29-1 | Thorium from Thorium nitrate hydrate | 0.001% |
| 7440-28-0 | Thallium from Thallium nitrate | 0.001% |
| 7440-61-1 | Uranium from Uranyl Nitrate Hexahydrate | 0.001% |
| 7440-62-2 | Vanadium from Ammonium trioxovanadate | 0.001% |
| 7440-66-6 | zinc powder -zinc dust (stabilized) | 0.001% |
| 7440-39-3 | Barium from Barium carbonate | 0.001% |
| 7440-38-2 | arsenic | 0.001% |
| 7440-22-4 | silver | 0.001% |
| 7429-90-5 | aluminium | 0.001% |
| 7732-18-5 | water, distilled, conductivity or of similar purity | 94.076% |

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 2)

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

| | | |
|-----------|---|--------------------------|
| 7697-37-2 | nitric acid | 0.16 ppm |
| 87-69-4 | (+)-tartaric acid | 1.6 mg/m ³ |
| 7782-49-2 | selenium | 0.6 mg/m ³ |
| 7440-41-7 | Beryllium from Beryllium Acetate | 0.0023 mg/m ³ |
| 7440-43-9 | cadmium (non-pyrophoric) | 0.10 mg/m ³ |
| 7440-48-4 | cobalt | 0.18 mg/m ³ |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate | 1.5 mg/m ³ |
| 7440-50-8 | copper | 3 mg/m ³ |
| 7439-96-5 | manganese | 3 mg/m ³ |
| 7439-98-7 | molybdenum | 30 mg/m ³ |
| 7440-02-0 | nickel | 4.5 mg/m ³ |
| 7439-92-1 | Lead from Lead Oxide | 0.15 mg/m ³ |
| 7440-36-0 | antimony | 1.5 mg/m ³ |
| 7440-29-1 | Thorium from Thorium nitrate hydrate | 30 mg/m ³ |
| 7440-28-0 | Thallium from Thallium nitrate | 0.06 mg/m ³ |
| 7440-61-1 | Uranium from Uranyl Nitrate Hexahydrate | 0.6 mg/m ³ |
| 7440-62-2 | Vanadium from Ammonium trioxovanadate | 3 mg/m ³ |
| 7440-66-6 | zinc powder -zinc dust (stabilized) | 6 mg/m ³ |
| 7440-39-3 | Barium from Barium carbonate | 1.5 mg/m ³ |
| 7440-38-2 | arsenic | 1.5 mg/m ³ |
| 7440-22-4 | silver | 0.3 mg/m ³ |

- **PAC-2:**

| | | |
|-----------|---|-------------------------|
| 7697-37-2 | nitric acid | 24 ppm |
| 87-69-4 | (+)-tartaric acid | 17 mg/m ³ |
| 7782-49-2 | selenium | 6.6 mg/m ³ |
| 7440-41-7 | Beryllium from Beryllium Acetate | 0.025 mg/m ³ |
| 7440-43-9 | cadmium (non-pyrophoric) | 0.76 mg/m ³ |
| 7440-48-4 | cobalt | 2 mg/m ³ |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate | 17 mg/m ³ |
| 7440-50-8 | copper | 33 mg/m ³ |
| 7439-96-5 | manganese | 5 mg/m ³ |
| 7439-98-7 | molybdenum | 330 mg/m ³ |
| 7440-02-0 | nickel | 50 mg/m ³ |
| 7439-92-1 | Lead from Lead Oxide | 120 mg/m ³ |
| 7440-36-0 | antimony | 13 mg/m ³ |
| 7440-29-1 | Thorium from Thorium nitrate hydrate | 330 mg/m ³ |
| 7440-28-0 | Thallium from Thallium nitrate | 3.3 mg/m ³ |
| 7440-61-1 | Uranium from Uranyl Nitrate Hexahydrate | 5 mg/m ³ |
| 7440-62-2 | Vanadium from Ammonium trioxovanadate | 5.8 mg/m ³ |
| 7440-66-6 | zinc powder -zinc dust (stabilized) | 21 mg/m ³ |
| 7440-39-3 | Barium from Barium carbonate | 180 mg/m ³ |
| 7440-38-2 | arsenic | 17 mg/m ³ |
| 7440-22-4 | silver | 170 mg/m ³ |

- **PAC-3:**

| | | |
|-----------|----------------------------------|-----------------------|
| 7697-37-2 | nitric acid | 92 ppm |
| 87-69-4 | (+)-tartaric acid | 100 mg/m ³ |
| 7782-49-2 | selenium | 40 mg/m ³ |
| 7440-41-7 | Beryllium from Beryllium Acetate | 0.1 mg/m ³ |

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 3)

| | | |
|-----------|---|-------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) | 4.7 mg/m ³ |
| 7440-48-4 | cobalt | 20 mg/m ³ |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate | 99 mg/m ³ |
| 7440-50-8 | copper | 200 mg/m ³ |
| 7439-96-5 | manganese | 1,800 mg/m ³ |
| 7439-98-7 | molybdenum | 2,000 mg/m ³ |
| 7440-02-0 | nickel | 99 mg/m ³ |
| 7439-92-1 | Lead from Lead Oxide | 700 mg/m ³ |
| 7440-36-0 | antimony | 80 mg/m ³ |
| 7440-29-1 | Thorium from Thorium nitrate hydrate | 2,000 mg/m ³ |
| 7440-28-0 | Thallium from Thallium nitrate | 20 mg/m ³ |
| 7440-61-1 | Uranium from Uranyl Nitrate Hexahydrate | 30 mg/m ³ |
| 7440-62-2 | Vanadium from Ammonium trioxovanadate | 35 mg/m ³ |
| 7440-66-6 | zinc powder -zinc dust (stabilized) | 120 mg/m ³ |
| 7440-39-3 | Barium from Barium carbonate | 1,100 mg/m ³ |
| 7440-38-2 | arsenic | 100 mg/m ³ |
| 7440-22-4 | silver | 990 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

| | |
|-----|--|
| PEL | Long-term value: 5 mg/m ³ , 2 ppm |
| REL | Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm |
| TLV | Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm |

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

| | |
|------------------|------------------------------------|
| Form: | Liquid |
| Color: | According to product specification |
| Odor: | Characteristic |
| Odour Threshold: | Not applicable. |

· pH-value: Not applicable.

· Change in condition

| | |
|------------------------------|------------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 83 °C (181.4 °F) |

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not applicable.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

| | |
|--------|-----------------|
| Lower: | Not applicable. |
| Upper: | Not applicable. |

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

· Density: Not applicable.

· Relative density: Not applicable.

· Vapor density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

| | |
|------------|-----------------|
| Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |

· Solvent content:

| | |
|--------------|--------|
| Water: | 94.1 % |
| VOC content: | 0.00 % |

Solids content: 0.9 %

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|---|----|
| 7782-49-2 | selenium | 3 |
| 7440-41-7 | Beryllium from Beryllium Acetate | 1 |
| 7440-43-9 | cadmium (non-pyrophoric) | 1 |
| 7440-48-4 | cobalt | 2B |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate | 3 |
| 7440-02-0 | nickel | 2B |
| 7439-92-1 | Lead from Lead Oxide | 2B |
| 7440-29-1 | Thorium from Thorium nitrate hydrate | 1 |
| 7440-38-2 | arsenic | 1 |

· **NTP (National Toxicology Program)**

| | | |
|-----------|----------------------------------|---|
| 7440-41-7 | Beryllium from Beryllium Acetate | K |
| 7440-43-9 | cadmium (non-pyrophoric) | K |
| 7440-48-4 | cobalt | R |
| 7440-02-0 | nickel | R |
| 7439-92-1 | Lead from Lead Oxide | R |
| 7440-38-2 | arsenic | K |

· **OSHA-Ca (Occupational Safety & Health Administration)**

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-38-2 | arsenic |

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A



(Contd. of page 6)

- *Must not reach bodies of water or drainage ditch undiluted or unneutralized.*
- *Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

| | |
|--|---|
| · UN-Number · DOT, ADR, IMDG, IATA | UN3264 |
| · UN proper shipping name · DOT · ADR · IMDG, IATA | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid Solution) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION) |
| · Transport hazard class(es) · DOT | |
|  | |
| · Class · Label | 8 Corrosive substances 8 |
| · ADR, IMDG, IATA | |
|  | |
| · Class · Label | 8 Corrosive substances 8 |
| · Packing group · DOT, ADR, IMDG, IATA | III |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code | Warning: Corrosive substances 80 F-A,S-B Acids A SW2 Clear of living quarters. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |

(Contd. on page 8)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 7)

| | |
|--|--|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION), 8, III</p> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 313 (Specific toxic chemical listings):**

| | |
|-----------|---|
| 7697-37-2 | nitric acid |
| 7782-49-2 | selenium |
| 7440-41-7 | Beryllium from Beryllium Acetate |
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-48-4 | cobalt |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate |
| 7440-50-8 | copper |
| 7439-96-5 | manganese |
| 7440-02-0 | nickel |
| 7439-92-1 | Lead from Lead Oxide |
| 7440-36-0 | antimony |
| 7440-28-0 | Thallium from Thallium nitrate |
| 7440-62-2 | Vanadium from Ammonium trioxovanadate |
| 7440-66-6 | zinc powder -zinc dust (stabilized) |
| 7440-39-3 | Barium from Barium carbonate |
| 7440-38-2 | arsenic |
| 7440-22-4 | silver |
| 7429-90-5 | aluminium |

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

| | |
|-----------|----------------------|
| 7440-48-4 | cobalt |
| 7439-96-5 | manganese |
| 7439-92-1 | Lead from Lead Oxide |

- **Proposition 65**

- **Chemicals known to cause cancer:**

| | |
|-----------|----------------------------------|
| 7440-41-7 | Beryllium from Beryllium Acetate |
| 7440-43-9 | cadmium (non-pyrophoric) |
| 7440-48-4 | cobalt |
| 7440-02-0 | nickel |
| 7439-92-1 | Lead from Lead Oxide |
| 7440-38-2 | arsenic |

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
|-----------|--------------------------|

- **Chemicals known to cause developmental toxicity:**

| | |
|-----------|--------------------------|
| 7440-43-9 | cadmium (non-pyrophoric) |
|-----------|--------------------------|

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

| | | |
|-----------|----------------------------------|-------------------------|
| 7782-49-2 | selenium | D |
| 7440-41-7 | Beryllium from Beryllium Acetate | BI, K/L(inh), CBD(oral) |

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 8)

| | | |
|-----------|-------------------------------------|-----------------------|
| 7440-43-9 | cadmium (non-pyrophoric) | B1 |
| 7440-50-8 | copper | D |
| 7439-96-5 | manganese | D |
| 7439-92-1 | Lead from Lead Oxide | B2 |
| 7440-66-6 | zinc powder -zinc dust (stabilized) | D, I, II |
| 7440-39-3 | Barium from Barium carbonate | D, CBD(inh), NL(oral) |
| 7440-38-2 | arsenic | A |
| 7440-22-4 | silver | D |

· **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|-----------|---|----|
| 7440-43-9 | cadmium (non-pyrophoric) | A2 |
| 7440-48-4 | cobalt | A3 |
| 7439-98-7 | molybdenum | A3 |
| 7440-02-0 | nickel | A5 |
| 7439-92-1 | Lead from Lead Oxide | A3 |
| 7440-61-1 | Uranium from Uranyl Nitrate Hexahydrate | A1 |
| 7440-39-3 | Barium from Barium carbonate | A4 |
| 7440-38-2 | arsenic | A1 |
| 7429-90-5 | aluminium | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

| | | |
|-----------|---|--|
| 7440-43-9 | cadmium (non-pyrophoric) | |
| 7440-02-0 | nickel | |
| 7440-61-1 | Uranium from Uranyl Nitrate Hexahydrate | |
| 7440-38-2 | arsenic | |

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05

· **Signal word** Danger

· **Hazard-determining components of labeling:**

nitric acid

· **Hazard statements**

H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 08/26/2019 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 10)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2019

Reviewed on 08/26/2019

Product Name: ICP-MS Instrument Calibration Standard 1A

(Contd. of page 9)

HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US