

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018

Reviewed on 10/23/2018

1 Identification

- **Product identifier**
- **Product Name:** Multi-element Solution 5
- **Part Number:** CLMS-5
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
Wash thoroughly after handling.
Wear protective gloves / eye protection / face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

- **HMS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

US

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018

Reviewed on 10/23/2018

Product Name: Multi-element Solution 5

(Contd. of page 1)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

7697-37-2	nitric acid	2.0%
-----------	-------------	------

- **Chemical identification of the substance/preparation**

7439-92-1	Lead from Lead Oxide	0.001%
7440-02-0	nickel	0.001%
7440-45-1	cerium	0.001%
7440-61-1	uranium	0.001%
7440-48-4	cobalt	0.001%
7440-69-9	bismuth	0.001%
7440-41-7	Beryllium from Beryllium Acetate	0.001%
7439-95-4	magnesium	0.001%
7440-74-6	indium	0.001%
7732-18-5	water, distilled, conductivity or of similar purity	97.991%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-I:**

7697-37-2	nitric acid	0.16 ppm
7439-92-1	Lead from Lead Oxide	0.15 mg/m ³
7440-02-0	nickel	4.5 mg/m ³
7440-45-1	cerium	30 mg/m ³
7440-61-1	uranium	0.6 mg/m ³
7440-48-4	cobalt	0.18 mg/m ³
7440-69-9	bismuth	15 mg/m ³
7440-41-7	Beryllium from Beryllium Acetate	0.0023 mg/m ³
7439-95-4	magnesium	18 mg/m ³

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018

Reviewed on 10/23/2018

Product Name: Multi-element Solution 5

(Contd. of page 2)

7440-74-6	indium	0.3 mg/m ³
· PAC-2:		
7697-37-2	nitric acid	24 ppm
7439-92-1	Lead from Lead Oxide	120 mg/m ³
7440-02-0	nickel	50 mg/m ³
7440-45-1	cerium	330 mg/m ³
7440-61-1	uranium	5 mg/m ³
7440-48-4	cobalt	2 mg/m ³
7440-69-9	bismuth	170 mg/m ³
7440-41-7	Beryllium from Beryllium Acetate	0.025 mg/m ³
7439-95-4	magnesium	200 mg/m ³
7440-74-6	indium	3.3 mg/m ³
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7439-92-1	Lead from Lead Oxide	700 mg/m ³
7440-02-0	nickel	99 mg/m ³
7440-45-1	cerium	2,000 mg/m ³
7440-61-1	uranium	30 mg/m ³
7440-48-4	cobalt	20 mg/m ³
7440-69-9	bismuth	990 mg/m ³
7440-41-7	Beryllium from Beryllium Acetate	0.1 mg/m ³
7439-95-4	magnesium	1,200 mg/m ³
7440-74-6	indium	20 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Product Name: Multi-element Solution 5

(Contd. of page 3)

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

pH-value: Not applicable.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

Flash point: Not applicable.

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not applicable.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not applicable.
Upper:	Not applicable.

Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

Density at 20 °C (68 °F) 1.01068 g/cm³ (8.43412 lbs/gal)

Relative density Not applicable.

Vapor density Not applicable.

Evaporation rate Not applicable.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not applicable.

Viscosity:

Dynamic:	Not applicable.
Kinematic:	Not applicable.

Solvent content:

Water:	98.0 %
VOC content:	0.00 %

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018

Reviewed on 10/23/2018

Product Name: Multi-element Solution 5

(Contd. of page 4)

Solids content: 0.0 %
Other information No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7439-92-1	Lead from Lead Oxide	2B
7440-02-0	nickel	2B
7440-48-4	cobalt	2B
7440-41-7	Beryllium from Beryllium Acetate	1

· **NTP (National Toxicology Program)**

7439-92-1	Lead from Lead Oxide	R
7440-02-0	nickel	R
7440-48-4	cobalt	R
7440-41-7	Beryllium from Beryllium Acetate	K

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018



Reviewed on 10/23/2018

Product Name: Multi-element Solution 5

(Contd. of page 5)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR · IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION)
· Transport hazard class(es) · DOT	
	
· Class · Label	8 Corrosive substances 8
· ADR, IMDG, IATA	
	
· Class · Label	8 Corrosive substances 8
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code	Warning: Corrosive substances 80 F-A,S-B Acids A SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION), 8, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 313 (Specific toxic chemical listings):**

7697-37-2 | nitric acid

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018

Reviewed on 10/23/2018

Product Name: Multi-element Solution 5

(Contd. of page 6)

7439-92-1	Lead from Lead Oxide
7440-02-0	nickel
7440-48-4	cobalt
7440-41-7	Beryllium from Beryllium Acetate

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

7439-92-1	Lead from Lead Oxide
7440-02-0	nickel
7440-48-4	cobalt
7440-41-7	Beryllium from Beryllium Acetate

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7439-92-1	Lead from Lead Oxide	B2
7440-41-7	Beryllium from Beryllium Acetate	B1, K/L(inh), CBD(oral)

· **TLV (Threshold Limit Value established by ACGIH)**

7439-92-1	Lead from Lead Oxide	A3
7440-02-0	nickel	A5
7440-61-1	uranium	A1
7440-48-4	cobalt	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0	nickel
7440-61-1	uranium

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· **Precautionary statements**

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 10/23/2018 / -

(Contd. on page 8)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/23/2018

Reviewed on 10/23/2018

Product Name: Multi-element Solution 5

(Contd. of page 7)

· Abbreviations and acronyms:*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

US