

1 Identification

- **Product identifier**
- **Product Name:** PAH Analyte Mix
- **Part Number:** ECS-B-032
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 2 H310 Fatal in contact with skin.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

benzene

dichloromethane

acenaphthylene

benzo[a]pyrene

- **Hazard statements**

H225 Highly flammable liquid and vapor.

(Contd. on page 2)

Product Name: PAH Analyte Mix

(Contd. of page 1)

H310 Fatal in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H360 May damage fertility or the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = *3
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:**

120-12-7	anthracene
----------	------------

· **vPvB:** Not applicable.**3 Composition/information on ingredients**· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

75-09-2	dichloromethane	48.4%
71-43-2	benzene	48.4%
120-12-7	anthracene	0.2%
56-55-3	benz[a]anthracene	0.2%
50-32-8	benzo[a]pyrene	0.2%
205-99-2	benz[e]acephenanthrylene	0.2%
191-24-2	Benzo(g,h,i)perylene	0.2%
207-08-9	benzo[k]fluoranthene	0.2%
218-01-9	chrysene	0.2%
53-70-3	dibenz[a,h]anthracene	0.2%
206-44-0	fluoranthene	0.2%
193-39-5	indeno[1,2,3-cd]pyrene	0.2%
91-20-3	naphthalene	0.2%
85-01-8	phenanthrene, pure	0.2%
129-00-0	pyrene	0.2%
· Chemical identification of the substance/preparation		
86-73-7	fluorene	0.2%
83-32-9	acenaphthene	0.2%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 2)

208-96-8 acenaphthylene

0.2%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting

- **Information for Doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

75-09-2	dichloromethane	200 ppm
71-43-2	benzene	52 ppm
120-12-7	anthracene	48 mg/m ³
56-55-3	benz[a]anthracene	0.6 mg/m ³
50-32-8	benzo[a]pyrene	0.6 mg/m ³
205-99-2	benz[e]acephenanthrylene	0.12 mg/m ³
191-24-2	Benzo(g,h,i)perylene	30 mg/m ³
218-01-9	chrysene	0.6 mg/m ³
53-70-3	dibenz[a,h]anthracene	0.093 mg/m ³
206-44-0	fluoranthene	8.2 mg/m ³
86-73-7	fluorene	6.6 mg/m ³
193-39-5	indeno[1,2,3-cd]pyrene	1.2 mg/m ³
91-20-3	naphthalene	15 ppm
85-01-8	phenanthrene, pure	5.4 mg/m ³
129-00-0	pyrene	0.15 mg/m ³
83-32-9	acenaphthene	3.6 mg/m ³
208-96-8	acenaphthylene	10 mg/m ³

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 3)

· PAC-2:		
75-09-2	dichloromethane	560 ppm
71-43-2	benzene	800 ppm
120-12-7	anthracene	530 mg/m ³
56-55-3	benz[a]anthracene	120 mg/m ³
50-32-8	benzo[a]pyrene	120 mg/m ³
205-99-2	benz[e]acephenanthrylene	1.3 mg/m ³
191-24-2	Benzo(g,h,i)perylene	330 mg/m ³
218-01-9	chrysene	12 mg/m ³
53-70-3	dibenz[a,h]anthracene	1 mg/m ³
206-44-0	fluoranthene	90 mg/m ³
86-73-7	fluorene	72 mg/m ³
193-39-5	indeno[1,2,3-cd]pyrene	13 mg/m ³
91-20-3	naphthalene	83 ppm
85-01-8	phenanthrene, pure	59 mg/m ³
129-00-0	pyrene	1.7 mg/m ³
83-32-9	acenaphthene	40 mg/m ³
208-96-8	acenaphthylene	110 mg/m ³
· PAC-3:		
75-09-2	dichloromethane	6,900 ppm
71-43-2	benzene	4000* ppm
120-12-7	anthracene	3,200 mg/m ³
56-55-3	benz[a]anthracene	700 mg/m ³
50-32-8	benzo[a]pyrene	700 mg/m ³
205-99-2	benz[e]acephenanthrylene	7.9 mg/m ³
191-24-2	Benzo(g,h,i)perylene	2,000 mg/m ³
218-01-9	chrysene	69 mg/m ³
53-70-3	dibenz[a,h]anthracene	2.9 mg/m ³
206-44-0	fluoranthene	400 mg/m ³
86-73-7	fluorene	430 mg/m ³
193-39-5	indeno[1,2,3-cd]pyrene	79 mg/m ³
91-20-3	naphthalene	500 ppm
85-01-8	phenanthrene, pure	360 mg/m ³
129-00-0	pyrene	110 mg/m ³
83-32-9	acenaphthene	240 mg/m ³
208-96-8	acenaphthylene	660 mg/m ³

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 5)

Product Name: PAH Analyte Mix

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

75-09-2 dichloromethane	
PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m ³ , 50 ppm BEI
71-43-2 benzene	
PEL	Short-term value: 15* mg/m ³ , 5* ppm Long-term value: 3* mg/m ³ , 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
TLV	Short-term value: 8 mg/m ³ , 2.5 ppm Long-term value: 1.6 mg/m ³ , 0.5 ppm Skin; BEI
56-55-3 benz[a]anthracene	
TLV	L; BEIp
50-32-8 benzo[a]pyrene	
PEL	Long-term value: 0.2 mg/m ³ see Coal tar pitch volatiles
REL	Long-term value: 0.1 mg/m ³ Coal tar pitch volatile; Pocket Guide Apps. A+C
TLV	L; BEIp
205-99-2 benz[e]acephenanthrylene	
TLV	L; BEIp
218-01-9 chrysene	
PEL	Long-term value: 0.2 mg/m ³ see Coal Tar Pitch Volatiles
REL	Long-term value: 0.1* mg/m ³ *Cyclohexane-extrble.fraction;PocketGuide Apps.A+C
TLV	L; BEIp
91-20-3 naphthalene	
PEL	Long-term value: 50 mg/m ³ , 10 ppm
REL	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
TLV	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
· Ingredients with biological limit values:	
75-09-2 dichloromethane	
BEI	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
71-43-2 benzene	
BEI	25 µg/g creatinine Medium: urine Time: end of shift Parameter: S-Phenylmercapturic acid (background)
	500 µg/g creatinine Medium: urine Time: end of shift Parameter: t,t-Muconic acid (background)

(Contd. on page 6)

Product Name: PAH Analyte Mix

(Contd. of page 5)

56-55-3 benz[a]anthracene

BEI -
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

50-32-8 benzo[a]pyrene

BEI -
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

205-99-2 benz[e]acephenanthrylene

BEI -
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

218-01-9 chrysene

BEI -
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 6)

· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	40 °C (104 °F)
· Flash point:	< 0 °C (<32 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	555 °C (1,031 °F)
· Decomposition temperature:	Not applicable.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	22 Vol %
· Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
· Density	Not applicable.
· Relative density	Not applicable.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not applicable.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	96.8 %
VOC content:	48.40 %
Solids content:	2.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

75-09-2 dichloromethane

Oral	LD50	1,600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)

71-43-2 benzene

Oral	LD50	4,894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LC50/4 h	9,980 mg/l (mouse)

91-20-3 naphthalene

Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat)

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 7)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Product is suspected to cause damage to fertility.
Product is suspected to cause birth defects.
The product can cause inheritable damage.

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
75-09-2	dichloromethane	2A
71-43-2	benzene	I
120-12-7	anthracene	3
56-55-3	benz[a]anthracene	2B
50-32-8	benzo[a]pyrene	I
205-99-2	benz[e]acephenanthrylene	2B
191-24-2	Benzo(g,h,i)perylene	3
207-08-9	benzo[k]fluoranthene	2B
218-01-9	chrysene	2B
53-70-3	dibenz[a,h]anthracene	2A
206-44-0	fluoranthene	3
86-73-7	fluorene	3
193-39-5	indeno[1,2,3-cd]pyrene	2B
91-20-3	naphthalene	2B
85-01-8	phenanthrene, pure	3
129-00-0	pyrene	3
83-32-9	acenaphthene	3

· **NTP (National Toxicology Program)**

75-09-2	dichloromethane	R
71-43-2	benzene	K
120-12-7	anthracene	R
56-55-3	benz[a]anthracene	R
50-32-8	benzo[a]pyrene	R
205-99-2	benz[e]acephenanthrylene	R
207-08-9	benzo[k]fluoranthene	R
218-01-9	chrysene	R
53-70-3	dibenz[a,h]anthracene	R
206-44-0	fluoranthene	R
86-73-7	fluorene	R
193-39-5	indeno[1,2,3-cd]pyrene	R
91-20-3	naphthalene	R
85-01-8	phenanthrene, pure	R
129-00-0	pyrene	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2	dichloromethane	
71-43-2	benzene	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**

· **PBT:**





120-12-7 anthracene

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
· **DOT, ADR, IMDG, IATA** UN1992
- **UN proper shipping name**
· **DOT** Flammable liquids, toxic, n.o.s. (Benzene, Dichloromethane)
· **ADR** 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (BENZENE, DICHLOROMETHANE), ENVIRONMENTALLY HAZARDOUS
· **IMDG** FLAMMABLE LIQUID, TOXIC, N.O.S. (BENZENE, DICHLOROMETHANE), MARINE POLLUTANT
· **IATA** FLAMMABLE LIQUID, TOXIC, N.O.S. (BENZENE, DICHLOROMETHANE)
- **Transport hazard class(es)**
- **DOT**

- **Class** 3 Flammable liquids
· **Label** 3, 6.1
- **ADR**

- **Class** 3 Flammable liquids
· **Label** 3+6.1
- **IMDG**

- **Class** 3 Flammable liquids
· **Label** 3/6.1
- **IATA**

- **Class** 3 Flammable liquids

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 9)

· Label	3 (6.1)
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: benzo[a]pyrene Symbol (fish and tree) Symbol (fish and tree)
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code	Warning: Flammable liquids 336 F-E,S-D Liquid halogenated hydrocarbons B SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (BENZENE, DICHLOROMETHANE), 3 (6.1), II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 313 (Specific toxic chemical listings):**

75-09-2	dichloromethane
71-43-2	benzene
120-12-7	anthracene
56-55-3	benz[a]anthracene
50-32-8	benzo[a]pyrene
205-99-2	benz[e]acephenanthrylene
191-24-2	Benzo(g,h,i)perylene
207-08-9	benzo[k]fluoranthene
218-01-9	chrysene
53-70-3	dibenz[a,h]anthracene
206-44-0	fluoranthene
193-39-5	indeno[1,2,3-cd]pyrene
91-20-3	naphthalene
85-01-8	phenanthrene, pure

· **TSCA (Toxic Substances Control Act):**

75-09-2	dichloromethane
71-43-2	benzene
120-12-7	anthracene
56-55-3	benz[a]anthracene
50-32-8	benzo[a]pyrene
218-01-9	chrysene
53-70-3	dibenz[a,h]anthracene
206-44-0	fluoranthene
86-73-7	fluorene
193-39-5	indeno[1,2,3-cd]pyrene

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 10)

91-20-3	naphthalene
85-01-8	phenanthrene, pure
129-00-0	pyrene
83-32-9	acenaphthene
208-96-8	acenaphthylene

· **TSCA new (21st Century Act): (Substances not listed)**

56-55-3	benz[a]anthracene
205-99-2	benz[e]acephenanthrylene
191-24-2	Benzo(g,h,i)perylene
207-08-9	benzo[k]fluoranthene
218-01-9	chrysene
53-70-3	dibenz[a,h]anthracene

· **Proposition 65**· **Chemicals known to cause cancer:**

75-09-2	dichloromethane
71-43-2	benzene
56-55-3	benz[a]anthracene
50-32-8	benzo[a]pyrene
205-99-2	benz[e]acephenanthrylene
207-08-9	benzo[k]fluoranthene
218-01-9	chrysene
53-70-3	dibenz[a,h]anthracene
193-39-5	indeno[1,2,3-cd]pyrene
91-20-3	naphthalene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

71-43-2	benzene
---------	---------

· **Chemicals known to cause developmental toxicity:**

71-43-2	benzene
---------	---------

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

75-09-2	dichloromethane	L
71-43-2	benzene	A, K/L
120-12-7	anthracene	D
56-55-3	benz[a]anthracene	B2
50-32-8	benzo[a]pyrene	CaH
205-99-2	benz[e]acephenanthrylene	B2
191-24-2	Benzo(g,h,i)perylene	D
207-08-9	benzo[k]fluoranthene	B2
218-01-9	chrysene	B2
53-70-3	dibenz[a,h]anthracene	B2
206-44-0	fluoranthene	D
86-73-7	fluorene	D
193-39-5	indeno[1,2,3-cd]pyrene	B2
91-20-3	naphthalene	C, CBD
85-01-8	phenanthrene, pure	D
129-00-0	pyrene	D
83-32-9	acenaphthene	A (oral)
208-96-8	acenaphthylene	D

· **TLV (Threshold Limit Value established by ACGIH)**

75-09-2	dichloromethane	A3
71-43-2	benzene	A1
56-55-3	benz[a]anthracene	A2
50-32-8	benzo[a]pyrene	A2

(Contd. on page 12)

Product Name: PAH Analyte Mix

(Contd. of page 11)

205-99-2	benz[e]acephenanthrylene	A2
218-01-9	chrysene	A3
91-20-3	naphthalene	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
75-09-2	dichloromethane	
71-43-2	benzene	
50-32-8	benzo[a]pyrene	
218-01-9	chrysene	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

benzene

dichloromethane

acenaphthylene

benzo[a]pyrene

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H310 Fatal in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 02/11/2019 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/11/2019

Reviewed on 02/11/2019

Product Name: PAH Analyte Mix

(Contd. of page 12)

HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEL: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 2: Acute toxicity – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1A: Carcinogenicity – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1

US