

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

1 Identification

- **Product identifier**
- **Trade name:** EPA Method 200.7 Calibration Standard 6
- **Article number:** ICP-200.7-6-A
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
High-Purity Standards
P.O. Box 41727
Charleston, SC 29423
Telephone: (843) 767-7900
FAX: (843) 767-7906
- **Information department:** Product safety department
- **Emergency telephone number:**
INFOTRAC
Emergency telephone numbers 1-800-535-5053
Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
nitric acid
Hydrofluoric acid
- **Hazard statements**
H290 May be corrosive to metals.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 1)

Precautionary statements

- Keep only in original container.
- Do not breathe dusts or mists.
- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If swallowed: Rinse mouth. Do NOT induce vomiting.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a poison center/doctor.
- Specific treatment (see on this label).
- Take off contaminated clothing and wash it before reuse.
- Wash contaminated clothing before reuse.
- Absorb spillage to prevent material damage.
- Store locked up.
- Store in corrosive resistant container with a resistant inner liner.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Other hazards

Results of PBT and vPvB assessment

- PBT:** Not applicable.
- vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

7697-37-2	nitric acid	2.0%
-----------	-------------	------

Chemical identification of the substance/preparation

7664-39-3	Hydrofluoric acid	0.49%
513-77-9	barium carbonate	0.002%
543-81-7	beryllium acetate	0.002%
10043-35-3	boric acid	0.002%
471-34-1	calcium carbonate	0.002%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 2)

7440-43-9	cadmium (non-pyrophoric)	0.002%
7440-47-3	chromium	0.002%
7440-48-4	cobalt	0.002%
7440-50-8	copper	0.002%
7439-89-6	iron	0.002%
7439-92-1	lead	0.002%
554-13-2	lithium carbonate	0.002%
7439-95-4	magnesium	0.002%
6156-78-1	Manganese(II) acetate tetrahydrate	0.002%
7439-98-7	molybdenum	0.002%
7440-02-0	nickel	0.002%
7722-76-1	Ammonium dihydrogenphosphate	0.002%
7757-79-1	potassium nitrate	0.002%
7782-49-2	selenium	0.002%
16919-19-0	ammonium hexafluorosilicate	0.002%
7440-22-4	silver	0.002%
497-19-8	sodium carbonate	0.002%
10042-76-9	strontium nitrate	0.002%
7440-28-0	thallium	0.002%
7440-31-5	tin	0.002%
7803-55-6	Ammonium Vanadate	0.002%
7440-66-6	zinc	0.002%
7440-36-0	antimony	0.002%
7440-38-2	arsenic	0.002%
7429-90-5	aluminium	0.002%
7732-18-5	water, distilled, conductivity or of similar purity	97.452%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

7697-37-2	nitric acid	0.16 ppm
7664-39-3	Hydrofluoric acid	1.0 ppm
513-77-9	barium carbonate	2.2 mg/m ³
10043-35-3	boric acid	6 mg/m ³
471-34-1	calcium carbonate	45 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	0.10 mg/m ³
7440-47-3	chromium	1.5 mg/m ³
7440-48-4	cobalt	0.18 mg/m ³
7440-50-8	copper	3 mg/m ³
7439-89-6	iron	3.2 mg/m ³
7439-92-1	lead	0.15 mg/m ³
554-13-2	lithium carbonate	3.1 mg/m ³
7439-95-4	magnesium	18 mg/m ³
6156-78-1	Manganese(II) acetate tetrahydrate	13 mg/m ³
7439-98-7	molybdenum	30 mg/m ³
7440-02-0	nickel	4.5 mg/m ³

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

		(Contd. of page 4)
7722-76-1	Ammonium dihydrogenphosphate	17 mg/m ³
7757-79-1	potassium nitrate	9 mg/m ³
7782-49-2	selenium	0.6 mg/m ³
16919-19-0	ammonium hexafluorosilicate	12 mg/m ³
7440-22-4	silver	0.3 mg/m ³
497-19-8	sodium carbonate	7.6 mg/m ³
10042-76-9	strontium nitrate	5.7 mg/m ³
7440-28-0	thallium	0.06 mg/m ³
7440-31-5	tin	6 mg/m ³
7803-55-6	Ammonium Vanadate	0.01 mg/m ³
7440-66-6	zinc	6 mg/m ³
7440-36-0	antimony	1.5 mg/m ³
7440-38-2	arsenic	1.5 mg/m ³

PAC-2:

7697-37-2	nitric acid	24 ppm
7664-39-3	Hydrofluoric acid	24 ppm
513-77-9	barium carbonate	270 mg/m ³
10043-35-3	boric acid	23 mg/m ³
471-34-1	calcium carbonate	210 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	0.76 mg/m ³
7440-47-3	chromium	17 mg/m ³
7440-48-4	cobalt	2 mg/m ³
7440-50-8	copper	33 mg/m ³
7439-89-6	iron	35 mg/m ³
7439-92-1	lead	120 mg/m ³
554-13-2	lithium carbonate	34 mg/m ³
7439-95-4	magnesium	200 mg/m ³
6156-78-1	Manganese(II) acetate tetrahydrate	22 mg/m ³
7439-98-7	molybdenum	330 mg/m ³
7440-02-0	nickel	50 mg/m ³
7722-76-1	Ammonium dihydrogenphosphate	190 mg/m ³
7757-79-1	potassium nitrate	100 mg/m ³
7782-49-2	selenium	6.6 mg/m ³
16919-19-0	ammonium hexafluorosilicate	130 mg/m ³
7440-22-4	silver	170 mg/m ³
497-19-8	sodium carbonate	83 mg/m ³
10042-76-9	strontium nitrate	62 mg/m ³
7440-28-0	thallium	3.3 mg/m ³
7440-31-5	tin	67 mg/m ³
7803-55-6	Ammonium Vanadate	0.11 mg/m ³

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 5)

7440-66-6	zinc	21 mg/m ³
7440-36-0	antimony	13 mg/m ³
7440-38-2	arsenic	17 mg/m ³
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7664-39-3	Hydrofluoric acid	44 ppm
513-77-9	barium carbonate	1,600 mg/m ³
10043-35-3	boric acid	830 mg/m ³
471-34-1	calcium carbonate	1,300 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	4.7 mg/m ³
7440-47-3	chromium	99 mg/m ³
7440-48-4	cobalt	20 mg/m ³
7440-50-8	copper	200 mg/m ³
7439-89-6	iron	150 mg/m ³
7439-92-1	lead	700 mg/m ³
554-13-2	lithium carbonate	210 mg/m ³
7439-95-4	magnesium	1,200 mg/m ³
6156-78-1	Manganese(II) acetate tetrahydrate	740 mg/m ³
7439-98-7	molybdenum	2,000 mg/m ³
7440-02-0	nickel	99 mg/m ³
7722-76-1	Ammonium dihydrogenphosphate	1,100 mg/m ³
7757-79-1	potassium nitrate	600 mg/m ³
7782-49-2	selenium	40 mg/m ³
16919-19-0	ammonium hexafluorosilicate	780 mg/m ³
7440-22-4	silver	990 mg/m ³
497-19-8	sodium carbonate	500 mg/m ³
10042-76-9	strontium nitrate	370 mg/m ³
7440-28-0	thallium	20 mg/m ³
7440-31-5	tin	400 mg/m ³
7803-55-6	Ammonium Vanadate	80 mg/m ³
7440-66-6	zinc	120 mg/m ³
7440-36-0	antimony	80 mg/m ³
7440-38-2	arsenic	100 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 6)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 7)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties
· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.· **Flammability (solid, gaseous):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)· **Density:** Not determined.· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**· **Dynamic:** Not determined.· **Kinematic:** Not determined.· **Solvent content:**· **Water:** 97.5 %

(Contd. on page 9)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 8)

VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	0.1 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

LD/LC50 values that are relevant for classification:		
7664-39-3 Hydrofluoric acid		
Oral	LD50	1,276 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

IARC (International Agency for Research on Cancer)		
543-81-7	beryllium acetate	1
7440-43-9	cadmium (non-pyrophoric)	1
7440-47-3	chromium	3
7440-48-4	cobalt	2B
7439-92-1	lead	2B
7440-02-0	nickel	2B
7782-49-2	selenium	3

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 9)

7440-38-2	arsenic	I
· NTP (National Toxicology Program)		
543-81-7	beryllium acetate	K
7440-43-9	cadmium (non-pyrophoric)	K
7440-48-4	cobalt	R
7439-92-1	lead	R
7440-02-0	nickel	R
7440-38-2	arsenic	K
· OSHA-Ca (Occupational Safety & Health Administration)		
7440-43-9	cadmium (non-pyrophoric)	
7440-38-2	arsenic	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN3264

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS


Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 10)

<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA 	<p><i>Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, Hydrogen fluoride)</i></p> <p><i>3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, Hydrogen fluoride)</i></p> <p>CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID, HYDROGEN FLUORIDE)</p>
---	---

<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<p></p>
<ul style="list-style-type: none"> · Class · Label 	<p>8 Corrosive substances</p> <p>8</p>

<ul style="list-style-type: none"> · ADR, IMDG, IATA 	<p></p>
<ul style="list-style-type: none"> · Class · Label 	<p>8 Corrosive substances</p> <p>8</p>

<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p>III</p>
---	------------

<ul style="list-style-type: none"> · Environmental hazards: 	<p><i>Not applicable.</i></p>
---	-------------------------------

<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code 	<p><i>Warning: Corrosive substances</i></p> <p><i>80</i></p> <p><i>F-A,S-B</i></p> <p><i>Acids</i></p> <p><i>A</i></p> <p><i>SW2 Clear of living quarters.</i></p>
--	--

<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p><i>Not applicable.</i></p>
--	-------------------------------

<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations 	<p><i>On passenger aircraft/rail: 5 L</i></p> <p><i>On cargo aircraft only: 60 L</i></p>
---	--

<ul style="list-style-type: none"> · ADR · Excepted quantities (EQ) 	<p><i>Code: E1</i></p> <p><i>Maximum net quantity per inner packaging: 30 ml</i></p> <p><i>Maximum net quantity per outer packaging: 1000 ml</i></p>
---	--

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 11)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID, HYDROGEN FLUORIDE), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

7697-37-2	nitric acid
7664-39-3	Hydrofluoric acid

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	nitric acid
7664-39-3	Hydrofluoric acid
513-77-9	barium carbonate
543-81-7	beryllium acetate
7440-43-9	cadmium (non-pyrophoric)
7440-47-3	chromium
7440-48-4	cobalt
7440-50-8	copper
7439-92-1	lead
554-13-2	lithium carbonate
7440-02-0	nickel
7757-79-1	potassium nitrate
7782-49-2	selenium
7440-22-4	silver
10042-76-9	strontium nitrate
7440-28-0	thallium
7803-55-6	Ammonium Vanadate
7440-66-6	zinc
7440-36-0	antimony
7440-38-2	arsenic
7429-90-5	aluminium

· **TSCA (Toxic Substances Control Act):**

7697-37-2	nitric acid
7664-39-3	Hydrofluoric acid

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 12)

513-77-9	barium carbonate
10043-35-3	boric acid
471-34-1	calcium carbonate
7440-43-9	cadmium (non-pyrophoric)
7440-47-3	chromium
7440-48-4	cobalt
7440-50-8	copper
7439-89-6	iron
7439-92-1	lead
554-13-2	lithium carbonate
7439-95-4	magnesium
7439-98-7	molybdenum
7440-02-0	nickel
7722-76-1	Ammonium dihydrogenphosphate
7757-79-1	potassium nitrate
7782-49-2	selenium
16919-19-0	ammonium hexafluorosilicate
7440-22-4	silver
497-19-8	sodium carbonate
10042-76-9	strontium nitrate
7440-28-0	thallium
7440-31-5	tin
7803-55-6	Ammonium Vanadate
7440-66-6	zinc
7440-36-0	antimony
7440-38-2	arsenic
7429-90-5	aluminium
7732-18-5	water, distilled, conductivity or of similar purity

· Proposition 65

· Chemicals known to cause cancer:

543-81-7	beryllium acetate
7440-43-9	cadmium (non-pyrophoric)
7440-48-4	cobalt
7439-92-1	lead
7440-02-0	nickel
7440-38-2	arsenic

· Chemicals known to cause reproductive toxicity for females:

7439-92-1	lead
-----------	------

· Chemicals known to cause reproductive toxicity for males:

7440-43-9	cadmium (non-pyrophoric)
-----------	--------------------------

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 13)

7439-92-1	lead
-----------	------

· Chemicals known to cause developmental toxicity:

7440-43-9	cadmium (non-pyrophoric)
7439-92-1	lead
554-13-2	lithium carbonate

· Carcinogenic categories

· EPA (Environmental Protection Agency) (Substances not listed)

7697-37-2	nitric acid
7664-39-3	Hydrofluoric acid
543-81-7	beryllium acetate
471-34-1	calcium carbonate
7440-48-4	cobalt
7439-89-6	iron
554-13-2	lithium carbonate
7439-95-4	magnesium
6156-78-1	Manganese(II) acetate tetrahydrate
7439-98-7	molybdenum
7440-02-0	nickel
7722-76-1	Ammonium dihydrogenphosphate
7757-79-1	potassium nitrate
16919-19-0	ammonium hexafluorosilicate
497-19-8	sodium carbonate
10042-76-9	strontium nitrate
7440-28-0	thallium
7440-31-5	tin
7803-55-6	Ammonium Vanadate
7440-36-0	antimony
7429-90-5	aluminium
7732-18-5	water, distilled, conductivity or of similar purity

· TLV (Threshold Limit Value established by ACGIH)

513-77-9	barium carbonate	A4
10043-35-3	boric acid	A4
7440-43-9	cadmium (non-pyrophoric)	A2
7440-47-3	chromium	A4
7440-48-4	cobalt	A3
7439-92-1	lead	A3
7439-98-7	molybdenum	A3
7440-02-0	nickel	A5
7440-38-2	arsenic	A1
7429-90-5	aluminium	A4

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 14)

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
7440-43-9	cadmium (non-pyrophoric)
7440-02-0	nickel
7440-38-2	arsenic

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
nitric acid
Hydrofluoric acid
- **Hazard statements**
H290 May be corrosive to metals.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
Keep only in original container.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
High-Purity Standards
Tel: 843-767-7900
Fax: 843-767-7906

(Contd. on page 16)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Reviewed on 03/29/2019

Trade name: EPA Method 200.7 Calibration Standard 6

(Contd. of page 15)

· Date of preparation / last revision 03/29/2019 / -**· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Met. Corr. 1: Corrosive to metals – Category 1**Acute Tox. 4: Acute toxicity – Category 4**Skin Corr. 1A: Skin corrosion/irritation – Category 1A**Eye Dam. 1: Serious eye damage/eye irritation – Category 1*