

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/17/2015 Revision date: 01/30/2018 Supersedes: 01/30/2018

Version: 1.1

### **SECTION 1: Identification**

Identification

Product form : Mixtures

Product name : p-Naphtholbenzein TS

Product code LC17530

Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.

Recommended use : Laboratory chemicals

Restrictions on use : Not for food, drug or household use

1.3. **Supplier** 

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

**Emergency telephone number** 

**Emergency number** : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

## SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

#### **GHS-US** classification

Flammable liquids H226 Flammable liquid and vapour

Category 3

Skin corrosion/irritation H314 Causes severe skin burns and eye damage Category 1B

Hazardous to the aquatic

environment - Acute

Hazard Category 3

Full text of H statements : see section 16

Harmful to aquatic life

# GHS Label elements, including precautionary statements

H402

# **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS02

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H226 - Flammable liquid and vapour

H314 - Causes severe skin burns and eye damage

H402 - Harmful to aquatic life

Precautionary statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe mist, vapors, spray.

P264 - Wash exposed skin thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

01/30/2018 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a poison center or doctor/physician.

P363 - Wash contaminated clothing before reuse.
P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to comply with local, state and federal regulations

#### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification

: None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

| Name              | Product identifier | %     | GHS-US classification  |
|-------------------|--------------------|-------|--|
| Acetic Acid       | (CAS-No.) 64-19-7  | 99.75 | Flam. Liq. 3, H226<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Aquatic Acute 3, H402 |
| p-Naphtholbenzein | (CAS-No.) 145-50-6 | 0.25  | Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319   |

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes severe skin burns and eye damage

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns

Symptoms/effects after eye contact : Corrosion of the eye tissue.

Symptoms/effects after ingestion : Nausea. Vomiting. Burns to the gastric/intestinal mucosa.

#### 4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Reactivity : Thermal decomposition generates : Corrosive vapors.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

01/30/2018 EN (English US) 2/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking.

6.1.1. For non-emergency personnel

Protective equipment : Protective goggles. Protective clothing. Gloves. Face-shield.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. No naked lights. No smoking. Take precautionary measures against static discharge.

Use only non-sparking tools. Do not breathe mist, vapors, spray.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/...

equipment. Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources,

Ignition sources, incompatible materials. Keep container tightly closed.

Incompatible products : Strong oxidizers. Strong bases.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Acetic Acid (64-19-7 | 7)                       |  |
|----------------------|--------------------------|--|
| ACGIH                | ACGIH TWA (ppm)          | 10 ppm (Acetic acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH                | ACGIH STEL (ppm)         | 15 ppm (Acetic acid; USA; Short time value; TLV - Adopted Value)                         |
| OSHA                 | OSHA PEL (TWA) (mg/m³)   | 25 mg/m <sup>3</sup>   |
| OSHA                 | OSHA PEL (TWA) (ppm)     | 10 ppm   |
| IDLH                 | US IDLH (ppm)            | 50 ppm   |
| NIOSH                | NIOSH REL (TWA) (mg/m³)  | 25 mg/m³   |
| NIOSH                | NIOSH REL (TWA) (ppm)    | 10 ppm   |
| NIOSH                | NIOSH REL (STEL) (mg/m³) | 37 mg/m³   |
| NIOSH                | NIOSH REL (STEL) (ppm)   | 15 ppm   |

#### p-Naphtholbenzein (145-50-6)

Not applicable

01/30/2018 EN (English US) 3/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

#### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Chemical resistant apron. Face shield. Gloves. Safety glasses. Protective clothing.









#### Hand protection:

Wear protective gloves.

#### Eye protection:

Chemical goggles or face shield

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Respiratory protection not required in normal conditions

#### Other information:

Do not eat, drink or smoke during use.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Color amber Odor : Vinegar odour Odor threshold : No data available рΗ : No data available Melting point : No data available Freezing point No data available Boiling point : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Flammable liquid and vapor.

Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available

Specific gravity / density : 1 g/ml

Solubility : Soluble in acetic acid. Soluble in water.

Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

01/30/2018 EN (English US) 4/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Thermal decomposition generates: Corrosive vapors.

#### 10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Strong oxidizers. Strong bases.

#### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. May release flammable gases. Thermal decomposition generates: Corrosive vapors.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

|                                      | Acetic Acid (64-19-7) |  |  |
|--------------------------------------|-----------------------|--|--|
|                                      | LD50 oral rat         | 3310 mg/kg body weight (Rat; Other; Read-across) |  |
| ATE US (oral) 3310 mg/kg body weight |                       | 3310 mg/kg body weight                           |  |

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Corrosion of the eye tissue.

Symptoms/effects after ingestion : Nausea. Vomiting. Burns to the gastric/intestinal mucosa.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - water : Harmful to aquatic life.

# 12.2. Persistence and degradability

| p-Naphtholbenzein TS          |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

01/30/2018 EN (English US) 5/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Acetic Acid (64-19-7)   |                             |  |
|---|-----------------------------|--|
| Persistence and degradability Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. |                             |  |
| Biochemical oxygen demand (BOD)   | 0.6 - 0.74 g O₂/g substance |  |
| Chemical oxygen demand (COD)  | 1.03 g O₂/g substance       |  |
| ThOD  | 1.07 g O₂/g substance       |  |

#### 12.3. **Bioaccumulative potential**

| p-Naphtholbenzein TS                       |  |  |  |
|--|--|--|--|
| Bioaccumulative potential Not established. |  |  |  |
| Acetic Acid (64-19-7)                      |  |  |  |
| BCF fish 1 3.16 (BCF; Pisces)              |  |  |  |
| Log Pow -0.17 (Experimental value; 25 ℃)   |  |  |  |
| Bioaccumulative potential                  | Low potential for bioaccumulation (Log Kow < 4). |  |  |

#### 12.4. Mobility in soil

| Acetic Acid (64-19-7)  |                    |  |
|--|--------------------|--|
| Surface tension  | 0.028 N/m (20 °C)  |  |
| Log Koc  | log Koc,0.06; QSAR |  |
| Ecology - soil May be harmful to plant growth, blooming and fruit formation. |                    |  |

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### **SECTION 13: Disposal considerations**

#### **Disposal methods**

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local, state and federal regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

: Avoid release to the environment. Ecology - waste materials

# **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN2789 Acetic acid solution, 8, II

UN-No.(DOT) : UN2789

Proper Shipping Name (DOT) : Acetic acid solution

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive

3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 243

01/30/2018 EN (English US) 6/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging.

A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging.

A7 - Steel packaging must be corrosion-resistant or have protection against corrosion. A10 - When aluminum or aluminum alloy construction materials are used, they must be resistant to corrosion.

B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C

(59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

: 154

# **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

| p-Naphtholbenzein TS                |  |  |
|-------------------------------------|--|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Fire hazard |  |

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

| Acetic Acid (64-19-7)  |         |  |
|--|---------|--|
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 5000 lb |  |

### 15.2. International regulations

### **CANADA**

### Acetic Acid (64-19-7)

Listed on the Canadian DSL (Domestic Substances List)

#### p-Naphtholbenzein (145-50-6)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

#### **Acetic Acid (64-19-7)**

Listed on the Canadian IDL (Ingredient Disclosure List)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

01/30/2018 EN (English US) 7/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| C | ECT | ION | 1 16: C | 1                                       | har in | forma | tion |
|---|-----|-----|---------|---|--------|-------|------|
|   |     |     | 4 IO. L | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, |        | ОПП   |      |

Revision date : 01/30/2018 Other information : None.

Full text of H-phrases: see section 16:

| iii text of Frepritases, see section To. |   |
|--|---|
| H226                                     | Flammable liquid and vapour             |
| H314                                     | Causes severe skin burns and eye damage |
| H315                                     | Causes skin irritation                  |
| H318                                     | Causes serious eye damage               |
| H319                                     | Causes serious eye irritation           |
| H402                                     | Harmful to aquatic life                 |

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard


: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even

under fire conditions.



Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability

\* - Chronic (long-term) health effects may result from repeated overexposure
: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above

100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: H

H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

# SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

01/30/2018 EN (English US) 8/8