

Safety Data Sheet acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

1 Identification

- **Product identifier**
- **Product Name:** Mixed Calibration Standard 4A
- **Part Name:**
MXSTD4A-100N
MXSTD4A-500N
- **Application of the substance / the mixture** *Certified Reference Material*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** *product safety department*
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS05

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
nitric acid
- **Hazard statements**
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
P303+P361+P353 *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P310 *Immediately call a poison center/doctor.*
P321 *Specific treatment (see on this label).*
P405 *Store locked up.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 1)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

7697-37-2	nitric acid	5.0%
7664-39-3	hydrofluoric acid	0.1%

- **Chemical identification of the substance/preparation**

7429-90-5	aluminium	0.01%
7440-32-6	titanium	0.01%
7631-86-9	silicon dioxide, chemically prepared	0.01%
7440-66-6	zinc	0.005%
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	0.005%
7440-31-5	tin	0.004%
7732-18-5	water, distilled, conductivity or of similar purity	94.856%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-I:**

7697-37-2	nitric acid	0.16 ppm
7440-32-6	titanium	30 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
7440-66-6	zinc	6 mg/m ³

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 2)

7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	1.5 mg/m ³
7440-31-5	tin	6 mg/m ³

· **PAC-2:**

7697-37-2	nitric acid	24 ppm
7440-32-6	titanium	330 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
7440-66-6	zinc	21 mg/m ³
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	17 mg/m ³
7440-31-5	tin	67 mg/m ³

· **PAC-3:**

7697-37-2	nitric acid	92 ppm
7440-32-6	titanium	2,000 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
7440-66-6	zinc	120 mg/m ³
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	99 mg/m ³
7440-31-5	tin	400 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 3)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

· **pH-value:** Not applicable.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	83 °C (181.4 83 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not applicable.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not applicable.
Upper:	Not applicable.

· **Vapor pressure at 20 °C (6820 °F):** 23 hPa (17.3 23 mm Hg)

· **Density at 20 °C (6820 °F)** 1.01749 g/cm³ (8.49095 1.01749 lbs/gal)

· **Relative density** Not applicable.

· **Vapor density** Not applicable.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not applicable.

· **Viscosity:**

Dynamic:	Not applicable.
Kinematic:	Not applicable.

· **Solvent content:**

Water:	94.9 %
VOC content:	0.00 %

Solids content: 0.0 %

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 4)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

7631-86-9	silicon dioxide, chemically prepared	3
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 6)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 5)

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR · IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution, Hydrofluoric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION, HYDROFLUORIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION, HYDROFLUORIC ACID)
· Transport hazard class(es) · DOT 	8 Corrosive substances 8
· ADR, IMDG, IATA 	8 Corrosive substances 8
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code	Warning: Corrosive substances 80 F-A,S-B Acids A SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION, HYDROFLUORIC ACID), 8, III

US

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 6)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	nitric acid
7664-39-3	hydrofluoric acid
7429-90-5	aluminium
7440-66-6	zinc
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate

· **TSCA (Toxic Substances Control Act):**

7697-37-2	nitric acid	ACTIVE
7429-90-5	aluminium	ACTIVE
7440-32-6	titanium	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
7440-66-6	zinc	ACTIVE
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	ACTIVE
7440-31-5	tin	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

7440-66-6	zinc	D, I, II
-----------	------	----------

· **TLV (Threshold Limit Value established by ACGIH)**

7429-90-5	aluminium	A4
-----------	-----------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS05

· **Signal word** Danger· **Hazard-determining components of labeling:**

nitric acid

· **Hazard statements**

H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/03/2019

Reviewed on 12/03/2019

Product Name: Mixed Calibration Standard 4A

(Contd. of page 7)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 12/03/2019 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US