

1 Identification

- **Product identifier**
- **Product Name:** Motor oil, SAE 30W
- **Part Number:** S-030W-20K
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

dichloromethane

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H351 Suspected of causing cancer.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/18/2019

Reviewed on 01/18/2019

Product Name: Motor oil, SAE 30W

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

75-09-2	dichloromethane	80.0%
---------	-----------------	-------

- **Chemical identification of the substance/preparation**

64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	20.0%
------------	---	-------

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Immediately call a doctor.
Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

Product Name: Motor oil, SAE 30W

(Contd. of page 2)

· **Protective Action Criteria for Chemicals**· **PAC-1:**

75-09-2	dichloromethane	200 ppm
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	140 mg/m ³

· **PAC-2:**

75-09-2	dichloromethane	560 ppm
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	1,500 mg/m ³

· **PAC-3:**

75-09-2	dichloromethane	6,900 ppm
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	8,900 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:****75-09-2 dichloromethane**

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m ³ , 50 ppm BEI

· **Ingredients with biological limit values:****75-09-2 dichloromethane**

BEI	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Respiratory protection:** Not required.
- **Protection of hands:**



Protective gloves

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/18/2019

Reviewed on 01/18/2019

Product Name: Motor oil, SAE 30W

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Liquid
· Color:	According to product specification
· Odor:	Characteristic
· Odour Threshold:	Not applicable.

- **pH-value:** Not applicable.

- **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	40 °C (104 °F)

- **Flash point:** < 0 °C (<32 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 605 °C (1,121 °F)

- **Decomposition temperature:** Not applicable.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

· Lower:	13 Vol %
· Upper:	22 Vol %

- **Vapor pressure at 20 °C (68 °F):** 453 hPa (339.8 mm Hg)

- **Density** Not applicable.

- **Relative density** Not applicable.

- **Vapor density** Not applicable.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not applicable.

- **Viscosity:**

· Dynamic:	Not applicable.
· Kinematic:	Not applicable.

- **Solvent content:**

· Organic solvents:	80.0 %
· VOC content:	0.00 %

· **Solids content:** 0.0 %

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/18/2019

Reviewed on 01/18/2019

Product Name: Motor oil, SAE 30W

(Contd. of page 4)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

75-09-2 dichloromethane

Oral	LD50	1,600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)

- **Primary irritant effect:**
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

75-09-2	dichloromethane	2A
---------	-----------------	----

- **NTP (National Toxicology Program)**

75-09-2	dichloromethane	R
---------	-----------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2	dichloromethane	
---------	-----------------	--

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1593
- **UN proper shipping name**
- **DOT** Dichloromethane

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 01/18/2019

Reviewed on 01/18/2019

Product Name: Motor oil, SAE 30W

(Contd. of page 5)

· ADR · IMDG, IATA	1593 Dichloromethane DICHLOROMETHANE
· Transport hazard class(es) · DOT	
	
· Class · Label	6.1 Toxic substances 6.1
· ADR, IMDG, IATA	
	
· Class · Label	6.1 Toxic substances 6.1
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups	Warning: Toxic substances 60 F-A,S-A Liquid halogenated hydrocarbons
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1593 DICHLOROMETHANE, 6.1, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 313 (Specific toxic chemical listings):

75-09-2 dichloromethane

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

75-09-2 dichloromethane

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/18/2019

Reviewed on 01/18/2019

Product Name: Motor oil, SAE 30W

(Contd. of page 6)

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

75-09-2 dichloromethane

L

- **TLV (Threshold Limit Value established by ACGIH)**

75-09-2 dichloromethane

A3

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

75-09-2 dichloromethane

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

dichloromethane

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H351 Suspected of causing cancer.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** product safety department

- **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

- **Date of preparation / last revision** 01/18/2019 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Carc. 2: Carcinogenicity – Category 2